

DAFTAR PUSTAKA

- A. A. Latif, Muh. Saleh Pallu, Farouk Maricar, Mukhsan Putra Hatta, (2019), *Pengaruh Tinggi Bukaannya Pintu Air Terhadap Bilangan Froude Dengan Dasar Tanah Lempung Pada Saluran Terbuka*, Fakultas Teknik, Universitas Muhammadiyah Surakarta, Prosiding Seminar Nasional 2019, ISSN : 2459-9727.
- Afifah Masruniwati, Farouk Maricar, Muksan Putra Hatta, (2020), *Pengaruh Bukaannya Pintu Terhadap Karakteristik Gerusan Sekitar Pintu Sorong Pada Saluran Terbuka*, Jurnal Penelitian Enjiniring (JPE) Bulan November, Vol. 24 No. 2.
- Albas J., & Permana S. 2016. *Kajian pengaruh tinggi bukaan pintu air tegak (Sluiceway) terhadap bilangan Froude*. Jurnal STT Garut.
- Aprilia Nurhayati, Very Dermawan, dan Heri Suprijanto (2016). *Jurnal Uji Model Fisik Gerusan Lokal Di Hilir Bukaannya Pintu Pada Dasar Saluran Pasir Bertanah Liat (Loamy Sand)*.
- Breuser, H.N.C., 1974-1975. *Lecture Notes on Sediment Transport 1*. International Course in Hydraulic Engineering, Delft.
- Muhammad Saleh Pallu. 2012. *Teori Dasar Angkutan Sedimen di Dalam Saluran Terbuka*. Makassar, Sulawesi Selatan. CV. Talaga Zam-zam.
- Ramayudha I.S.J. (2020). *Jurnal Pengaruh Tinggi Bukaannya Pintu Air terhadap Karakteristik Aliran*.
- Rijn, Leo C Van., 1987. *Mathematical Modelling of Morphological Processes in The Case of Suspended Sediment Transport*. Thesis approved by the Delft University of Technology, Delft Hydraulics Communication.
- Sucipto dan Nur Qudus. 2004. *Analisis Gerusan Lokal di Hilir Bed Protection*. *Jurnal Teknik Sipil dan Perencanaan*. Nomer 1 Volume 6. Januari 2004. Semarang : UNNE.
- Triatmodjo, B. 2011 *Hidraulika II*. Beta Offset Yogyakarta.
- Triatmodjo, B. 2014. *Hidraulika II*. Yogyakarta. Beta Offset.
- Ven Te Chow. 1992. *Aliran melalui saluran terbuka*. Jakarta : Erlangga. Simon & Senturk. 1976. *Sediment Transport Technology*, USA: Water Resources Publication.

- Yang, C.T., 1996. *Sediment Transport: Theory and Practice*. Singapore: The McGraw-Hill Companies, Inc.
- Yen, J., C.H. L. & Tsai, C., 2001. *Hydroulic Characteristic and Discharge Control of Sluice Gate*. Journal of the Chinese Institue of Engineers Vol. 24 No. 3 pp. 301-310.

LAMPIRAN

Tinggi Dasar Flum

Upstream

Jarak	0	10	20	30	40	50	60	70	80	90	100
As	20.28	20.21	20.15	20.18	20.05	20.06	20.03	20.02	20.07	20.1	20.12

Downstream

Jarak	0	10	20	30	40	50	60	70	80	90	100
As	20.28	20.35	20.38	20.36	20.38	20.41	20.46	20.61	20.65	20.62	20.63

Tinggi Muka Air S = 0%

Upstream

Jarak	0	10	20	30	40	50	60	70	80	90	100
As	24.36	24.32	24.38	24.36	24.38	24.43	24.32	24.36	24.30	24.30	24.30

Downstream

Jarak	0	10	20	30	40	50	60	70	80	90	100
As	24.36	24.43	24.41	24.50	24.50	24.52	24.57	24.80	24.80	24.86	24.80

Upstream

Jarak	0	10	20	30	40	50	60	70	80	90	100
As	4.09	4.11	4.23	4.18	4.33	4.37	4.29	4.34	4.23	4.20	4.18

Downstream

Jarak	0	10	20	30	40	50	60	70	80	90	100
As	4.09	4.08	4.03	4.14	4.12	4.11	4.11	4.19	4.15	4.24	4.17

Tinggi Muka Air S = 0.90%

Upstream

Jarak	0	10	20	30	40	50	60	70	80	90	100
As	22.13	22.03	22.02	21.87	21.90	21.81	21.91	21.77	21.91	21.73	21.90

Downstream

Jarak	0	10	20	30	40	50	60	70	80	90	100
As	22.13	22.19	22.20	22.16	22.20	22.21	22.24	22.43	22.35	22.46	22.40

Upstream

Jarak	0	10	20	30	40	50	60	70	80	90	100
As	1.86	1.82	1.87	1.69	1.85	1.75	1.88	1.75	1.84	1.63	1.78

Downstream

Jarak	0	10	20	30	40	50	60	70	80	90	100
As	1.86	1.84	1.82	1.80	1.82	1.80	1.78	1.82	1.70	1.84	1.77

Tinggi Muka Air S = 1.80%

Upstream

Jarak	0	10	20	30	40	50	60	70	80	90	100
As	22.03	21.79	21.67	21.67	21.69	21.75	21.71	21.67	21.65	21.67	21.75

Downstream

Jarak	0	10	20	30	40	50	60	70	80	90	100
As	22.03	22.09	22.00	22.02	21.98	22.01	22.05	22.27	22.28	22.21	22.22

Upstream

Jarak	0	10	20	30	40	50	60	70	80	90	100
As	1.76	1.58	1.52	1.49	1.64	1.69	1.68	1.65	1.58	1.57	1.63

Downstream

Jarak	0	10	20	30	40	50	60	70	80	90	100
As	1.76	1.74	1.62	1.66	1.60	1.60	1.59	1.66	1.63	1.59	1.59