

DAFTAR PUSTAKA

- Suendri.2018.Implementasi Diagram UML (Unified Modelling Language) Pada Perancangan Sistem *Informasi* Remunerasi Dosen Dengan Database Oracle (Studi Kasus: UIN Sumatera Utara Medan).Jurnal Ilmu Komputer dan InFormatika,Vol.03, No.01
- Sulthoni,A.2018.Sistem *Informasi* E-Commerce Pemasaran Hasil Pertanian Desa Kluwan Berbasis *Web*.Jurusan Teknologi *Informasi* dan Komputer, STEKOM Semarang.
- Tiket Pesawat Di Total Nusa Indonesia *Tour And Travel* Yogyakarta.Jurnal Media Wisata, Vol. 12, No.1
- Hendini,ade.2016. Pemodelan Uml Sistem *Informasi* Monitoring Penjualan Dan Stok Barang (Studi Kasus: Distro Zhezha Pontianak). Jurnal khatulistiwa inFormatika, Vol. 4, No. 2
- HAM, H. 2018. Kelebihan Menggunakan Laravel *Web* Development.<https://socs.binus.ac.id/2018/12/13/kelebihan-menggunakan-laravel-web-development/>
- Mulyani, Sri. 2016. Sistem Informasi Manajemen. Bandung: Abdi Sistematika.
- Sutabri, T. 2012. Analisis Sistem Informasi. Yogyakarta: Andi.
- Chakti, A. G. 2019. The Book of Digital Marketing. Celebes Media Perkasa.
- Muslihudin, M., & Oktafianto. 2016. Analisis dan Perancangan Sistem Informasi Menggunakan Model Terstruktur dan UML. ANDI.
- Mulyani, S. 2016. Analisis dan Perancangan Sistem Informasi Manajemen Keuangan Daerah: Notasi Pemodelan Unified Modeling Language (UML). ABDI SISTEMATIKA.
- Hidayat, Rahmat. 2010. Cara Praktis Membangun *Website* Gratis Memanfaatkan Layanan Domain dan Hosting Gratis. Jakarta: PT Elex Media Komputindo.
- Suryatiningsih, Wardani Muhammad. 2008. Pemrograman *Web*. Bandung: Politeknik Telkom.
- Laravel. 2023. Laravel Documentation Version 10.x. Diakses dari <https://laravel.com/docs/10.x>

R. Susanto dan A. D. Andriana, "Perbandingan Model *Waterfall* dan Prototyping untuk Pengembangan Sistem Informasi," Majalah Ilmiah UNIKOM

Setiawan, R. 2021. *Black box Testing* Untuk Menguji Perangkat Lunak. Diakses dari <https://www.dicoding.com/blog/black-box-testing/>

LAMPIRAN

Link Code: bit.ly/Code-H071171508

Booking Controller

```
<?php

namespace App\Http\Controllers\Admin;

use App\Models\User;
use App\Models\Booking;
use App\Models\Package;
use Illuminate\Http\Request;
use App\Http\Controllers\Controller;
use App\Http\Requests\Admin\BookingRequest;
use Symfony\Component\HttpFoundation\Response;

class BookingController extends Controller
{
    /**
     * Display a listing of the resource.
     *
     * @return \Illuminate\Http\Response
     */
    public function index()
    {
        return view('admin.bookings.index',[
            'bookings' => Booking::with(['details','package','user'])->get()
        ]);
    }

    /**
     * Show the form for creating new Booking.
     *
     * @return \Illuminate\Http\Response
     */
    public function create(Request $request)
    {
        $packages = Package::get()->pluck('destination', 'id');
        $packageId = $request->get('package');

        return view('admin.bookings.create', compact('packages', 'packageId'));
    }

    /**
```

```

* Store a newly created resource in storage.
*
* @param \Illuminate\Http\Request $request
* @return \Illuminate\Http\Response
*/
public function store(BookingRequest $request)
{

    Booking::create($request->validated());

    return redirect()->route('admin.bookings.index')->with([
        'message' => 'successfully created !',
        'alert-type' => 'success'
    ]);
}

/**
 * Display Booking.
 *
 * @param int $id
 * @return \Illuminate\Http\Response
 */
public function show(Booking $booking)
{

    $booking = Booking::with([
        'details', 'package', 'user'
    ])->findOrFail($booking->id);
    return view('admin.bookings.show', compact('booking'));
}

/**
 * Show the form for editing the specified resource.
 *
 * @param int $id
 * @return \Illuminate\Http\Response
 */
public function edit(Booking $booking)
{

}

/**
 * Update the specified resource in storage.
 *
 * @param \Illuminate\Http\Request $request
 * @param int $id
 * @return \Illuminate\Http\Response
 */

```

```

public function update(BookingRequest $request, Booking $booking)
{

    $booking->update($request->validated());

    return redirect()->route('admin.bookings.index')->with([
        'message' => 'successfully updated !',
        'alert-type' => 'info'
    ]);
}

/**
 * Remove the specified resource from storage.
 *
 * @param int $id
 * @return \Illuminate\Http\Response
 */
public function destroy(Booking $booking)
{

    $booking->delete();

    return redirect()->route('admin.bookings.index')->with([
        'message' => 'successfully deleted !',
        'alert-type' => 'danger'
    ]);
}

/**
 * Delete all selected Permission at once.
 *
 * @param Request $request
 */
public function massDestroy(Request $request)
{

    Booking::whereIn('id', request('ids'))->delete();

    return response()->noContent();
}
}

```

Category Controller

```

<?php

namespace App\Http\Controllers\Admin;

```

```
use App\Models\Category;
use Illuminate\Http\Request;
use App\Http\Controllers\Controller;

use App\Http\Requests\Admin\CategoryRequest;
use Symfony\Component\HttpFoundation\Response;

class CategoryController extends Controller
{
    /**
     * Display a listing of the resource.
     *
     * @return \Illuminate\Http\Response
     */
    public function index()
    {

        $categories = Category::all();

        return view('admin.categories.index', compact('categories'));
    }

    /**
     * Show the form for creating a new resource.
     *
     * @return \Illuminate\Http\Response
     */
    public function create()
    {

        return view('admin.categories.create');
    }

    /**
     * Store a newly created resource in storage.
     *
     * @param \Illuminate\Http\Request $request
     * @return \Illuminate\Http\Response
     */
    public function store(CategoryRequest $request)
    {

        Category::create($request->validated());

        return redirect()->route('admin.categories.index')->with([
            'message' => 'successfully created !',
        ]);
    }
}
```

```

        'alert-type' => 'success'
    ]);
}

/**
 * Show the form for editing the specified resource.
 *
 * @param int $id
 * @return \Illuminate\Http\Response
 */
public function edit(Category $category)
{

    return view('admin.categories.edit', compact('category'));
}

/**
 * Update the specified resource in storage.
 *
 * @param \Illuminate\Http\Request $request
 * @param int $id
 * @return \Illuminate\Http\Response
 */
public function update(CategoryRequest $request, Category $category)
{

    $category->update($request->validated());

    return redirect()->route('admin.categories.index')->with([
        'message' => 'successfully updated !',
        'alert-type' => 'info'
    ]);
}

/**
 * Remove the specified resource from storage.
 *
 * @param int $id
 * @return \Illuminate\Http\Response
 */
public function destroy(Category $category)
{

    $category->delete();

    return redirect()->route('admin.categories.index')->with([
        'message' => 'successfully deleted !',
        'alert-type' => 'danger'
    ]);
}

```

```

    });
}

/**
 * Delete all selected Permission at once.
 *
 * @param Request $request
 */
public function massDestroy(Request $request)
{
    Category::whereIn('id', request('ids'))->delete();

    return response()->noContent();
}
}

```

Country Controller

```

<?php

namespace App\Http\Controllers\Admin;

use App\Models\Country;
use Illuminate\Http\Request;
use App\Http\Controllers\Controller;
use App\Http\Requests\Admin\CountryRequest;
use Symfony\Component\HttpFoundation\Response;

class CountryController extends Controller
{
    /**
     * Display a listing of the resource.
     *
     * @return \Illuminate\Http\Response
     */
    public function index()
    {

        $countries = Country::all();

        return view('admin.countries.index', compact('countries'));
    }

    /**
     * Show the form for creating a new resource.
     *
     * @return \Illuminate\Http\Response
     */
}

```



```

public function create()
{
    return view('admin.countries.create');
}

/**
 * Store a newly created resource in storage.
 *
 * @param \Illuminate\Http\Request $request
 * @return \Illuminate\Http\Response
 */
public function store(CountryRequest $request)
{
    Country::create($request->validated());

    return redirect()->route('admin.countries.index')->with([
        'message' => 'successfully created !',
        'alert-type' => 'success'
    ]);
}

/**
 * Show the form for editing the specified resource.
 *
 * @param int $id
 * @return \Illuminate\Http\Response
 */
public function edit(Country $country)
{
    return view('admin.countries.edit', compact('country'));
}

/**
 * Update the specified resource in storage.
 *
 * @param \Illuminate\Http\Request $request
 * @param int $id
 * @return \Illuminate\Http\Response
 */
public function update(CountryRequest $request, Country $country)
{
    $country->update($request->validated());

    return redirect()->route('admin.countries.index')->with([
        'message' => 'successfully updated !',
        'alert-type' => 'info'
    ]);
}

```

```

    ]);
}

/**
 * Remove the specified resource from storage.
 *
 * @param int $id
 * @return \Illuminate\Http\Response
 */
public function destroy(Country $country)
{
    $country->delete();

    return redirect()->route('admin.countries.index')->with([
        'message' => 'successfully deleted !',
        'alert-type' => 'danger'
    ]);
}

/**
 * Delete all selected Permission at once.
 *
 * @param Request $request
 */
public function massDestroy(Request $request)
{
    Country::whereIn('id', request('ids'))->delete();

    return response()->noContent();
}
}

```

Dashboard Controller

```

<?php

namespace App\Http\Controllers\Admin;

use App\Models\User;
use App\Models\Booking;
use Illuminate\Http\Request;
use App\Http\Controllers\Controller;

class DashboardController extends Controller
{
    public function index(){
        $userCount = User::where('roles', 'USER')->count();
        $totalTransaction = Booking::where('transaction_status', 'SUCCESS')->sum('transaction_total');
    }
}

```

```

        $pendingStatusCount = Booking::where('transaction_status', 'PENDING')-
        >count();
        $successStatusCount = Booking::where('transaction_status', 'SUCCESS')-
        >count();

        return view('admin.dashboard', compact('userCount',
        'totalTransaction','pendingStatusCount','successStatusCount'));
    }
}

```

Gallery Controller

```

<?php

namespace App\Http\Controllers\Admin;

use App\Models\Gallery;
use Illuminate\Support\Str;
use Illuminate\Http\Request;
use App\Models\Package;
use App\Http\Controllers\Controller;
use App\Http\Requests\Admin\GalleryRequest;

class GalleryController extends Controller
{
    /**
     * Display a listing of the resource.
     *
     * @return \Illuminate\Http\Response
     */
    public function index()
    {
        return view('admin.gallery.index',[
            'items' => Gallery::with(['packages'])->get()
        ]);
    }

    /**
     * Show the form for creating a new resource.
     *
     * @return \Illuminate\Http\Response
     */
    public function create()
    {
        $packages = Package::get()->pluck('destination', 'id');

        return view('admin.gallery.create', compact('packages'));
    }
}

```

```

/**
 * Store a newly created resource in storage.
 *
 * @param \Illuminate\Http\Request $request
 * @return \Illuminate\Http\Response
 */
public function store(GalleryRequest $request)
{
    $data = $request->all();
    $data['image'] = $request->file('image')->store(
        'assets/gallery','public'
    );

    Gallery::create($data);
    return redirect()->route('admin.gallery.index');
}

/**
 * Display the specified resource.
 *
 * @param int $id
 * @return \Illuminate\Http\Response
 */
public function show($id)
{
    //
}

/**
 * Show the form for editing the specified resource.
 *
 * @param int $id
 * @return \Illuminate\Http\Response
 */
public function edit($id)
{
    return view('admin.gallery.edit',[
        'item' => Gallery::findOrFail($id),
        'packages' => Package::all()
    ]);
}

/**
 * Update the specified resource in storage.
 *
 * @param \Illuminate\Http\Request $request
 * @param int $id
 * @return \Illuminate\Http\Response

```

```

*/
public function update(GalleryRequest $request, $id)
{
    $data = $request->all();
    $data['image'] = $request->file('image')->store(
        'assets/gallery','public'
    );
    $item = Gallery::findOrFail($id)->update($data);

    return redirect()->route('admin.gallery.index');
}

/**
 * Remove the specified resource from storage.
 *
 * @param int $id
 * @return \Illuminate\Http\Response
 */
public function destroy($id)
{
    $item =Gallery::findOrFail($id);
    $item->delete();

    return redirect()->route('admin.gallery.index');
}
}

```

Package Controller

```

<?php

namespace App\Http\Controllers\Admin;

use App\Models\Package;
use App\Models\Booking;
use App\Models\Category;
use Illuminate\Http\Request;
use App\Http\Controllers\Controller;
use Illuminate\Support\Facades\Gate;
use App\Http\Requests\Admin\PackageRequest;
use Symfony\Component\HttpFoundation\Response;

class PackageController extends Controller
{
    /**
     * Display a listing of the resource.
     *
     * @return \Illuminate\Http\Response
     */
    public function index()

```

```

{
    $packages = Package::all();

    return view('admin.packages.index', compact('packages'));
}

/**
 * Show the form for creating a new resource.
 *
 * @return \Illuminate\Http\Response
 */
public function create()
{
    $categories = Category::get()->pluck('name', 'id');

    return view('admin.packages.create', compact('categories'));
}

/**
 * Store a newly created resource in storage.
 *
 * @param \Illuminate\Http\Request $request
 * @return \Illuminate\Http\Response
 */
public function store(PackageRequest $request)
{
    Package::create($request->validated());

    return redirect()->route('admin.packages.index')->with([
        'message' => 'successfully created !',
        'alert-type' => 'success'
    ]);
}

/**
 * Display Package.
 *
 * @param int $id
 * @return \Illuminate\Http\Response
 */
public function show(Package $package)
{
    $bookings = Booking::where('packages_id', $package->id)->get();

    $groupedBookings = $bookings->groupBy(function ($booking) {
        return $booking->user->email;
    });
}

```

```

    })->map(function ($group) {
        return [
            'user' => $group->first()->user->email,
            'total_price' => $group->sum('transaction_total'),
            'duration' => $group->count(),
            'destination' => $group->first()->package->destination,
        ];
    });
    return view('admin.packages.show', compact('package',
'groupedBookings'));
}

/**
 * Show the form for editing the specified resource.
 *
 * @param int $id
 * @return \Illuminate\Http\Response
 */
public function edit(Package $package)
{
    $categories = Category::get()->pluck('name', 'id');

    return view('admin.packages.edit', compact('package', 'categories'));
}

/**
 * Update the specified resource in storage.
 *
 * @param \Illuminate\Http\Request $request
 * @param int $id
 * @return \Illuminate\Http\Response
 */
public function update(PackageRequest $request, Package $package)
{
    $package->update($request->validated());

    return redirect()->route('admin.packages.index')->with([
        'message' => 'successfully updated !',
        'alert-type' => 'info'
    ]);
}

/**
 * Remove the specified resource from storage.
 *
 * @param int $id
 * @return \Illuminate\Http\Response
 */
public function destroy(Package $package)

```

```

{
    $package->bookings()->delete();
    $package->delete();

    return redirect()->route('admin.packages.index')->with([
        'message' => 'successfully deleted !',
        'alert-type' => 'danger'
    ]);
}

/**
 * Delete all selected Permission at once.
 *
 * @param Request $request
 */
public function massDestroy(Request $request)
{
    Package::whereIn('id', request('ids'))->delete();

    return response()->noContent();
}
}

```

User Controller

```

<?php

namespace App\Http\Controllers\Admin;

use App\Models\User;
use App\Http\Controllers\Controller;
use Illuminate\Support\Facades\Request;
use App\Http\Requests\Admin\StoreUserRequest;
use App\Http\Requests\Admin\UpdateUserRequest;

class UserController extends Controller
{
    /**
     * Display a listing of the resource.
     *
     * @return \Illuminate\Http\Response
     */
    public function index()
    {
        $users = User::all();

        return view('admin.users.index', compact('users'));
    }
}

```



```

}

/**
 * Show the form for creating a new resource.
 *
 * @return \Illuminate\Http\Response
 */
public function create()
{
    return view('admin.users.create');
}

/**
 * Store a newly created resource in storage.
 *
 * @param \Illuminate\Http\Request $request
 * @return \Illuminate\Http\Response
 */
public function store(StoreUserRequest $request)
{
    $user = User::create($request->validated() + ['password' => bcrypt($request->password)]);

    return redirect()->route('admin.users.index')->with([
        'message' => 'successfully created !',
        'alert-type' => 'success'
    ]);
}

/**
 * Show the form for editing the specified resource.
 *
 * @param int $id
 * @return \Illuminate\Http\Response
 */
public function edit(User $user)
{
    return view('admin.users.edit', compact('user'));
}

/**
 * Update the specified resource in storage.
 *
 * @param \Illuminate\Http\Request $request
 * @param int $id
 * @return \Illuminate\Http\Response
 */
public function update(UpdateUserRequest $request, User $user)
{

```

```

    $user->update($request->validated() + ['password' => bcrypt($request->password)]);

    return redirect()->route('admin.users.index')->with([
        'message' => 'successfully updated !',
        'alert-type' => 'info'
    ]);
}

/**
 * Remove the specified resource from storage.
 *
 * @param int $id
 * @return \Illuminate\Http\Response
 */
public function destroy(User $user)
{
    $user->delete();

    return redirect()->route('admin.users.index')->with([
        'message' => 'successfully deleted !',
        'alert-type' => 'danger'
    ]);
}

/**
 * Delete all selected Permission at once.
 *
 * @param Request $request
 */
public function massDestroy(Request $request)
{
    User::whereIn('id', request('ids'))->delete();

    return response()->noContent();
}
}

```

Checkout Controller

```

<?php

namespace App\Http\Controllers;

use Carbon\Carbon;
use Midtrans\Snap;
use Midtrans\Config;
use App\Models\Booking;
use App\Models\Country;
use App\Models\Package;

```

```

use Illuminate\Http\Request;
use App\Models\BookingDetail;
use App\Mail\TransactionSuccess;
use App\Http\Controllers\Controller;
use Illuminate\Support\Facades\Auth;
use Illuminate\Support\Facades\Mail;

class CheckoutController extends Controller
{
    public function index(Request $request, $id)
    {
        $item = Booking::with(['details', 'package', 'user'])->findOrFail($id);
        $countries = Country::all();
        return view('pages.checkout', [
            'item' => $item,
            'countries' => $countries
        ]);
    }

    public function process(Request $request, $id)
    {
        $package = Package::findOrFail($id);

        $bookings = Booking::create([
            'packages_id' => $id,
            'users_id' => Auth::user()->id,
            'transaction_total' => 0,
            'transaction_status' => 'IN_CART'
        ]);

        return redirect()->route('checkout', $bookings->id);
    }

    public function remove(Request $request, $detail_id)
    {
        $item = BookingDetail::findOrFail($detail_id);

        $bookings = Booking::with(['details', 'package'])
            ->findOrFail($item->bookings_id);

        $bookings->transaction_total -= $bookings->package->price;

        $bookings->save();
        $item->forceDelete();

        return redirect()->route('checkout', $item->bookings_id);
    }

    public function create(Request $request, $id)
    {

```

```

$request->validate([
    'nama_lengkap' => 'required|string|max:255',
    'email' => 'required|string|email|max:255|unique:booking_details,email',
    'numberphone' => 'required|string|max:255|unique:booking_details,numberphone',
    'tanggal_lahir' => 'required|date',
    'kewarganegaraan' => 'required|string|max:255',
], [
    'nama_lengkap.required' => 'Harap isi Nama Lengkap.',
    'email.required' => 'Harap isi Email.',
    'email.email' => 'Format Email tidak valid.',
    'email.unique' => 'Email sudah digunakan.',
    'numberphone.email' => 'Format Nomor Telepon tidak valid.',
    'numberphone.unique' => 'Nomor Telepon sudah digunakan.',
    'tanggal_lahir.required' => 'Harap isi Tanggal Lahir.',
    'tanggal_lahir.date' => 'Format Tanggal Lahir tidak valid.',
    'kewarganegaraan.required' => 'Harap isi Kewarganegaraan.',
]);

$data = $request->all();
$data['bookings_id'] = $id;

$country = Country::where('name', $request->kewarganegaraan)->first();
$data['kewarganegaraan'] = $country->name;

BookingDetail::create($data);

$bookings = Booking::with(['package','details'])->find($id);
$bookings->transaction_total += $bookings->package->price + mt_rand(1,
999);

$bookings->save();

return redirect()->route('checkout', $id);
}

public function success(Request $request, $id)
{
    $transaction = Booking::with(['details','package.galleries','user'])
->findOrFail($id);
    $transaction->transaction_status = 'PENDING';

    $transaction->save();

    // Cek apakah ada booking details terkait
    if ($transaction->details->isEmpty()) {
        return redirect()->route('checkout', $id)->with([
            'message' => 'Tolong isi Data Pengunjungnya',
            'alert-type' => 'danger'
        ]);
    }
}

```

```

    ]);
}

//set konfigurasi midtrans
Config::$serverKey = config('midtrans.serverKey');
Config::$isProduction = config('midtrans.isProduction');
Config::$isSanitized = config('midtrans.isSanitized');
Config::$is3ds = config('midtrans.is3ds');

//buat array buat dikirim ke midtrans
$midtrans_params = [
    'transaction_details' => [
        'order_id' => 'TEST-' . $transaction->id . '-' . time(),
        // 'order_id' => 'TEST-' . $transaction->id,
        'gross_amount' => (int) $transaction->transaction_total,
    ],
    'customer_details' => [
        'first_name' => $transaction->user->name,
        'email' => $transaction->user->email,
    ],
    'enable_payments' => ['bank-transfer'],
    'vtweb' => [],
];

try {
    //ambil halaman payment midtrans
    $paymentUrl = Snap::createTransaction($midtrans_params)->redirect_url;

    //simpan Snap token ke dalam model Booking
    $transaction->update(['snap_token' => $paymentUrl]);

    //redirect ke halaman midtrans
    header('Location: ' . $paymentUrl);
} catch (Exception $e) {
    echo $e->getMessage();
}
}
}

```

Detail Controller

```

<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;
use App\Models\Package;
use App\Http\Controllers\Controller;

```

```

class DetailController extends Controller
{
    public function index(Request $request, $id){

        return view('pages.detail',[
            'item'=>Package::with('galleries')->where('id',$id)->firstOrFail()
        ]);
    }
}

```

Home Controller

```

<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;
use App\Models\Package;
use App\Http\Controllers\Controller;

class HomeController extends Controller
{

    public function index()
    {
        $packages = Package::with('galleries')
            ->limit(6)
            ->latest()
            ->get();

        // Tambahkan nilai default untuk $searchKeyword
        $searchKeyword = "";

        return view('pages.home', compact('packages', 'searchKeyword'));
    }

    public function search(Request $request)
    {
        $searchKeyword = $request->input('search');

        $packages = Package::latest()
            ->when($searchKeyword, function ($query) use ($searchKeyword) {
                return $query->search($searchKeyword);
            })
            ->limit(6)
            ->latest()
            ->get();

        return view('pages.offer', compact('packages', 'searchKeyword'));
    }
}

```

```

    }

    public function ajaxSearch(Request $request)
    {
        $searchKeyword = $request->input('search');

        $results = Package::select('destination', 'location')
            ->where('destination', 'like', '%' . $searchKeyword . '%')
            ->orWhere('location', 'like', '%' . $searchKeyword . '%')
            ->limit(5)
            ->get();

        return response()->json($results);
    }
}

```

Midtrans Controller

```

<?php

namespace App\Http\Controllers;

use Midtrans\Config;
use App\Models\Booking;
use Midtrans\Notification;
use Illuminate\Http\Request;
use App\Mail\TransactionSuccess;
use App\Http\Controllers\Controller;
use Illuminate\Support\Facades\Mail;
use Illuminate\Support\Facades\Redirect;

class MidtransController extends Controller
{
    public function notificationHandler(Request $request){

        //set konfigurasi midtrans
        Config::$serverKey = config('midtrans.serverKey');
        Config::$isProduction = config('midtrans.isProduction');
        Config::$isSanitized = config('midtrans.isSanitized');
        Config::$is3ds = config('midtrans.is3ds');

        //Buat instance midtrans notification
        $notification = new Notification();

        //pecah order id agar bisa diterima oleh database
        $order = explode('-', $notification->order_id);

        //assign ke variabel untuk memudahkan coding

```

```

$status = $notification->transaction_status;
$type = $notification->payment_type;
$fraud = $notification->fraud_status;
$order_id = $order[1];

//cari transaksi berdasarkan ID
$booking = Booking::with('details')->findOrFail($order_id);

//handle notifikasi status midtrans
if($status == 'capture'){
    if ($type == 'credit_card') {
        if ($fraud == 'challenge') {
            $booking->transaction_status = "CHALLENGE";
        }else{
            $booking->transaction_status = "SUCCESS";
        }
    }
}
elseif ($status == 'settlement') {
    $booking->transaction_status = "SUCCESS";
}
elseif ($status == 'pending') {
    $booking->transaction_status = "PENDING";
}
}
elseif ($status == 'deny') {
    $booking->transaction_status = "FAILED";
}
}
elseif ($status == 'expire') {
    $booking->transaction_status = "EXPIRED";
}
}
elseif ($status == 'cancel') {
    $booking->transaction_status = "FAILED";
}
}
//simpan transaksi
$booking->save();

//kirirkan email
if($booking){
    if($status == 'capture' && $fraud == 'accept'){
        Mail::to($booking->user)->send(
            new TransactionSuccess($booking, $notification->order_id)
        );
    }
    else if($status == 'settlement') {
        Mail::to($booking->user)->send(
            new TransactionSuccess($booking, $notification->order_id)
        );
    }
}
}

```



```

else if($status =='success' ){
    Mail::to($booking->user)->send(
        new TransactionSuccess($booking, $notification->order_id)
    );
}
else if($status =='capture' && $fraud == 'challenge' ){
    return response()->json([
        'meta' =>[
            'code' =>200,
            'message' => 'Midtrans Payment Challenge'
        ]
    ]);
}
else{
    return response()->json([
        'meta' =>[
            'code' =>200,
            'message' => 'Midtrans Payment not Settlement'
        ]
    ]);
}

return response()->json([
    'meta' =>[
        'code' =>200,
        'message' => 'Midtrans Notification Success'
    ]
]);
}
}
}

```

```

public function finishRedirect(Request $request)
{
    $orderId = $request->input('order_id');
    $statusCode = $request->input('status_code');
    $transactionStatus = $request->input('transaction_status');

    // Lakukan pengecekan kondisi yang sesuai, misalnya status_code 201 dan
    transaction_status pending
    if ($statusCode == 201 && $transactionStatus == 'pending') {
        // Redirect ke halaman unfinish
        return view('pages.unfinish');
    }

    // Logika lainnya jika kondisi tidak terpenuhi, misalnya redirect ke halaman
    success
    // Gantilah 'success' dengan halaman yang sesuai

```

```

return view('pages.success');
}

public function unfinishRedirect()
{
    return view('pages.unfinish');
}

public function errorRedirect()
{
    return view('pages.failed');
}

public function redirectToPayment(Request $request, $orderId)
{
    // Ambil informasi pesanan berdasarkan ID
    $booking = Booking::findOrFail($orderId);

    // Pastikan status transaksi masih PENDING
    if ($booking->transaction_status === 'PENDING') {
        // Lakukan pengalihan ke halaman pembayaran Midtrans menggunakan
        Snap token
        $payment_url = $booking->snap_token;

        // Redirect pengguna ke halaman pembayaran
        return redirect()->away($payment_url);
    } else {
        // Jika status transaksi bukan PENDING, Anda dapat menangani kasus ini
        sesuai kebutuhan
        // Misalnya, tampilkan pesan kesalahan atau arahkan pengguna ke
        halaman lain
        return redirect()->route('home');
    }
}
}
}

```

My Transaction Controller

```

<?php

namespace App\Http\Controllers;

use App\Models\User;
use App\Models\Booking;
use App\Models\Package;
use Illuminate\Http\Request;
use App\Http\Controllers\Controller;

```

```

class MytransactionController extends Controller
{
    public function index(Request $request, $userId){

        $user = User::findOrFail($userId);

        $mytransactions = Booking::with(['details', 'package'])
        ->where('users_id', $userId)
        ->latest('created_at')
        ->get();

        return view('pages.mytransaction', [
            'user' => $user,
            'mytransactions' => $mytransactions,
        ]);
    }
}

```

Offer Controller

```

<?php

namespace App\Http\Controllers;

use App\Models\Package;
use App\Models\Category;
use Illuminate\Http\Request;
use App\Http\Controllers\Controller;

class OfferController extends Controller
{
    public function index(){

        $categories = Category::get()->pluck('name', 'id');
        $packages = Package::with(['galleries'])->limit(6)->latest()->get();
        return view('pages.offer', compact('packages', 'categories'));
    }
}

```

Model Booking

```

<?php

namespace App\Models;

use Carbon\Carbon;
use App\Models\User;
use App\Models\Package;
use App\Models\BookingDetail;
use Illuminate\Database\Eloquent\Model;

```

```

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Support\Str;

class Booking extends Model
{
    use HasFactory;

    protected $fillable = [
        'packages_id',
        'users_id',
        'transaction_total',
        'transaction_status',
        'snap_token',
        'created_at',
        'updated_at',
    ];

    public function package(){
        return $this->belongsTo(Package::class, 'packages_id','id');
    }

    public function details(){
        return $this->hasMany(BookingDetail::class,'bookings_id','id');
    }

    public function user()
    {
        return $this->belongsTo(User::class,'users_id','id');
    }
}

```

Model Booking Detail

```

<?php

namespace App\Models;

use Carbon\Carbon;
use App\Models\User;
use App\Models\Package;
use App\Models\BookingDetail;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Support\Str;

class Booking extends Model
{
    use HasFactory;

```

```

protected $fillable = [
    'packages_id',
    'users_id',
    'transaction_total',
    'transaction_status',
    'snap_token',
    'created_at',
    'updated_at',
];

public function package(){
    return $this->belongsTo(Package::class, 'packages_id','id');
}

public function details(){
    return $this->hasMany(BookingDetail::class,'bookings_id','id');
}

public function user()
{
    return $this->belongsTo(User::class,'users_id','id');
}
}

```

Category

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Model;
use Cviebrock\EloquentSluggable\Sluggable;
use Illuminate\Database\Eloquent\Factories\HasFactory;

class Category extends Model
{
    use HasFactory ,Sluggable;

    protected $guarded = ['id', 'created_at', 'updated_at'];

    /**
     * Return the sluggable configuration array for this model.
     *
     * @return array
     */
    public function sluggable(): array
    {

```

```

return [
    'slug' => [
        'source' => 'name',
        'onUpdate' => 'true'
    ]
];
}
}

```

Model Country

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Country extends Model
{
    use HasFactory;

    protected $guarded = ['id', 'created_at', 'updated_at'];
}

```

Model Gallery

```

<?php

namespace App\Models;

use App\Models\Package;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Database\Eloquent\SoftDeletes;
use Illuminate\Database\Eloquent\Factories\HasFactory;

class Gallery extends Model
{
    use HasFactory, SoftDeletes;
    protected $fillable = [
        'packages_id', 'image'
    ];

    protected $hidden = [

    ];

    public function packages(){
        return $this->belongsTo(Package::class, 'packages_id', 'id');
    }
}

```

```
}
}
```

Model Package

```
<?php

namespace App\Models;

use App\Models\Galery;
use App\Models\Booking;
use App\Models\Gallery;
use App\Models\Category;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\SoftDeletes;

class Package extends Model
{
    use HasFactory,SoftDeletes;

    protected $fillable =[
        'destination',
        'location',
        'description',
        'price',
        'duration',
        'date',
        'category_id',
        'bookings_id'
    ];

    public function category() {
        return $this->belongsTo(Category::class);
    }

    public function bookings() {
        return $this->hasMany(Booking::class, 'packages_id');
    }

    public function galleries() {
        return $this->hasMany(Gallery::class,'packages_id','id');
    }

    public function scopeSearch($query, $searchKeyword)
    {
        return $query->where('destination', 'like', '% . $searchKeyword . %')
            ->orWhere('location', 'like', '% . $searchKeyword . %');
    }
}
```

Model User

```
<?php

namespace App\Models;

use Laravel\Sanctum\HasApiTokens;
use Illuminate\Notifications\Notifiable;
use Illuminate\Contracts\Auth\MustVerifyEmail;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Foundation\Auth\User as Authenticatable;

class User extends Authenticatable implements MustVerifyEmail
{
    use HasApiTokens, HasFactory, Notifiable;

    /**
     * The attributes that are mass assignable.
     *
     * @var array<int, string>
     */
    protected $fillable = [
        'email',
        'roles',
        'password',
    ];

    /**
     * The attributes that should be hidden for serialization.
     *
     * @var array<int, string>
     */
    protected $hidden = [
        'password',
        'remember_token',
    ];

    /**
     * The attributes that should be cast.
     *
     * @var array<string, string>
     */
    protected $casts = [
        'email_verified_at' => 'datetime',
    ];
}
```


Mail Transaction Success

```

<?php

namespace App\Mail;

use Illuminate\Bus\Queueable;
use Illuminate\Contracts\Queue\ShouldQueue;
use Illuminate\Mail\Mailable;
use Illuminate\Queue\SerializesModels;

class TransactionSuccess extends Mailable
{
    use Queueable, SerializesModels;

    public $data;
    public $order_id;
    /**
     * Create a new message instance.
     *
     * @return void
     */
    public function __construct($data, $order_id)
    {
        $this->data = $data;
        $this->order_id = $order_id;
    }

    /**
     * Build the message.
     *
     * @return $this
     */
    public function build()
    {
        return $this
            ->from('fiyastravel@gmail.com','FiyasTravel')
            ->subject('E-Tiket Trip Anda',)
            ->view('email.transaction-success');
    }
}

```

Migration Countries Table

```

<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

class CreateCountriesTable extends Migration
{

```

```

/**
 * Run the migrations.
 *
 * @return void
 */
public function up()
{
    Schema::create('countries', function (Blueprint $table) {
        $table->id();
        $table->string('name');
        $table->string('shortcode')->nullable();
        $table->timestamps();
    });
}

/**
 * Reverse the migrations.
 *
 * @return void
 */
public function down()
{
    Schema::dropIfExists('countries');
}
}

```

Migration Users Table

```

<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

class CreateUsersTable extends Migration
{
    /**
     * Run the migrations.
     *
     * @return void
     */
    public function up()
    {
        Schema::create('users', function (Blueprint $table) {
            $table->id();
            $table->string('email')->unique();
            $table->string('roles')->default('USER'); //USER,ADMIN
            $table->timestamp('email_verified_at')->nullable();
            $table->string('password');
            $table->rememberToken();
        });
    }
}

```

```

        $table->timestamps();
    });
}

/**
 * Reverse the migrations.
 *
 * @return void
 */
public function down()
{
    Schema::dropIfExists('users');
}
}

```

Migration Galleries Table

```

<?php

use App\Models\Package;
use Illuminate\Support\Facades\Schema;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Database\Migrations\Migration;

class CreateGalleriesTable extends Migration
{
    /**
     * Run the migrations.
     *
     * @return void
     */
    public function up()
    {
        Schema::create('galleries', function (Blueprint $table) {
            $table->id();
            $table->integer('packages_id');
            $table->text('image');
            $table->softDeletes();
            $table->timestamps();
        });
    }

    /**
     * Reverse the migrations.
     *
     * @return void
     */
    public function down()
    {
        Schema::dropIfExists('galleries');
    }
}

```

```
}
}
```

Migration Booking Details

```
<?php

use App\Models\Country;
use Illuminate\Support\Facades\Schema;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Database\Migrations\Migration;

class CreateBookingDetailsTable extends Migration
{
    /**
     * Run the migrations.
     *
     * @return void
     */
    public function up()
    {
        Schema::create('booking_details', function (Blueprint $table) {
            $table->id();
            $table->integer('bookings_id');
            $table->string('nama_lengkap');
            $table->date('tanggal_lahir');
            $table->string('email');
            $table->string('numberphone');
            $table->string('kewarganegaraan');
            $table->foreignIdFor(Country::class)->nullable()->constrained()-
>cascadeOnUpdate();
            $table->softDeletes();
            $table->timestamps();
        });
    }

    /**
     * Reverse the migrations.
     *
     * @return void
     */
    public function down()
    {
        Schema::dropIfExists('booking_details');
    }
}
```

Migration Categories Table

```
<?php
```

```

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

class CreateCategoriesTable extends Migration
{
    /**
     * Run the migrations.
     *
     * @return void
     */
    public function up()
    {
        Schema::create('categories', function (Blueprint $table) {
            $table->id();
            $table->string('name');
            $table->string('slug')->unique();
            $table->timestamps();
        });
    }

    /**
     * Reverse the migrations.
     *
     * @return void
     */
    public function down()
    {
        Schema::dropIfExists('categories');
    }
}

```

Migration Packages Table

```

<?php

use App\Models\Category;
use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

class CreatePackagesTable extends Migration
{
    /**
     * Run the migrations.
     *
     * @return void
     */
    public function up()

```

```

{
    Schema::create('packages', function (Blueprint $table) {
        $table->id();
        $table->string('destination');
        $table->text('location')->nullable();
        $table->text('description')->nullable();
        $table->text('price')->nullable();
        $table->text('duration')->nullable();
        $table->date('date')->nullable();
        $table->integer('bookings_id')->nullable();
        $table->foreignIdFor(Category::class)->nullable()->constrained()-
>cascadeOnUpdate();

        $table->timestamps();
        $table->softDeletes();

        $table->index(['deleted_at']);
    });
}

/**
 * Reverse the migrations.
 *
 * @return void
 */
public function down()
{
    Schema::dropIfExists('packages');
}
}

```

Migration Bookings Table

```

<?php

use App\Models\Package;
use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

class CreateBookingsTable extends Migration
{
    /**
     * Run the migrations.
     *
     * @return void
     */
    public function up()
    {
        Schema::create('bookings', function (Blueprint $table) {

```

```

        $table->id();
        $table->integer('transaction_total');
        $table-
>string('transaction_status');//IN_CART,PENDING,SUCCESS,CANCEL,FAILED
        $table->integer('users_id')->nullable();
        $table->integer('packages_id')->constrained()->cascadeOnDelete();

        $table->timestamps();
        $table->softDeletes();

        $table->index(['deleted_at']);
    });
}

/**
 * Reverse the migrations.
 *
 * @return void
 */
public function down()
{
    Schema::dropIfExists('bookings');
}
}

```

Migration Add Snap Token Bookings Table

```

<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

class AddSnapTokenToBookingsTable extends Migration
{
    /**
     * Run the migrations.
     *
     * @return void
     */
    public function up()
    {
        Schema::table('bookings', function (Blueprint $table) {
            $table->string('snap_token')->nullable()->after('transaction_status');
        });
    }

    /**
     * Reverse the migrations.
     *

```

```

* @return void
*/
public function down()
{
    Schema::table('bookings', function (Blueprint $table) {
        $table->dropColumn('snap_token');
    });
}
}

```

View Admin Booking Edit

```

@extends('layouts.admin')

@section('content')
    <div class="container-fluid">

        @if ($errors->any())
            <div class="alert alert-danger">
                <ul>
                    @foreach ($errors->all() as $error)
                        <li>{{ $error }}</li>
                    @endforeach
                </ul>
            </div>
        @endif

        <!-- Content Row -->
        <div class="card shadow">
            <div class="card-header py-3 d-flex">
                <h1 class="h3 mb-0 text-gray-800">{{ __('edit booking') }}</h1>
                <div class="ml-auto">
                    <a href="{{ route('admin.bookings.index') }}" class="btn btn-primary">
                        <span class="text">{{ __('Go Back') }}</span>
                    </a>
                </div>
            </div>
            <div class="card-body">
                <form action="{{ route('admin.bookings.update', $booking->id) }}"
method="POST">
                    @csrf
                    @method('put')
                    <div class="form-group">
                        <label for="package">{{ __('Package') }}</label>
                        <select class="form-control" name="packages_id" id="package">
                            @foreach ($packages as $id => $package)
                                <option value="{{ $id }}">{{ $package }}</option>
                            @endforeach
                        </select>
                    </div>
                </div>
            </div>
        </div>
    </div>

```



```

        <div class="form-group">
            <label for="status">{{ __('Status') }}</label>
            <select class="form-control" name="status" id="status">
                <option value="0" {{ $booking->transaction_status == 0 ?
'selected' : null }}>Created
                </option>
                <option value="1" {{ $booking->transaction_status == 1 ?
'selected' : null }}>Completed
                </option>
                <option value="2" {{ $booking->transaction_status == 2 ?
'selected' : null }}>Cancelled
                </option>
            </select>
        </div>
        <button type="submit" class="btn btn-primary btn-block">{{ __('Save')
}}</button>
    </form>
</div>
</div>

<!-- Content Row -->

</div>
@endsection

@push('style-alt')
<link rel="stylesheet"
href="https://cdnjs.cloudflare.com/ajax/libs/bootstrap-
datetimepicker/4.17.47/css/bootstrap-datetimepicker.min.css">
@endpush

@push('script-alt')
<script
src="https://cdn.datatables.net/select/1.2.0/js/dataTables.select.min.js"></script>
<script
src="https://cdnjs.cloudflare.com/ajax/libs/moment.js/2.20.1/moment.min.js"></sc
ript>
<script
src="https://cdnjs.cloudflare.com/ajax/libs/bootstrap-
datetimepicker/4.17.47/js/bootstrap-datetimepicker.min.js">
</script>
<script>
    $('<span>.</span>datetimepicker').datetimepicker({
        format: "YYYY-MM-DD HH:mm"
    });
</script>
@endpush

```

View Admin Booking Index

```

@extends('layouts.admin')

@section('content')
  <div class="container-fluid">

    <!-- Page Heading -->

    <!-- Content Row -->
    <div class="card">
      <div class="card-header py-3 d-flex">
        <h6 class="m-0 font-weight-bold text-primary">
          {{ __('Booking') }}
        </h6>
      </div>
      <div class="card-body">
        <div class="table-responsive">
          <table class="table table-bordered table-striped table-hover datatable
datatable-booking" cellspacing="0"
          width="100%">
            <thead>
              <tr>
                <th width="10">

                </th>
                <th>No</th>
                <th>Email Customer</th>
                <th>Destination</th>
                <th>Date</th>
                <th>Status</th>
                <th>Action</th>
              </tr>
            </thead>
            <tbody>
              @forelse($bookings as $booking)
                <tr data-entry-id="{{ $booking->id }}">
                  <td>

                  </td>
                  <td>{{ $loop->iteration }}</td>
                  <td>{{ $booking->user->email }}</td>
                  <td>{{ $booking->package->destination }}</td>
                  <td>{{ \Carbon\Carbon::parse($booking->package->date)-
>translatedFormat('d F Y') }}</td>
                  <td>{{ $booking->transaction_status }}</td>
                  <td>
                    <a href="{{ route('admin.bookings.show', $booking->id)
}}}" class="btn btn-info">

```

```

        <i class="fa fa-eye"></i>
      </a>
      <form onclick="return confirm('are you sure ? ')"
class="d-inline"
      action="{{ route('admin.bookings.destroy', $booking-
>id) }}" method="POST">
        @csrf
        @method('delete')
        <button class="btn btn-danger">
          <i class="fa fa-trash"></i>
        </button>
      </form>
    </td>
  </tr>
  @empty
  <tr>
    <td colspan="9" class="text-center">{{ __('Data Empty')
}}</td>
  </tr>
  @endforelse
</tbody>
</table>
</div>
</div>
<!-- Content Row -->

</div>
@endsection

@push('script-alt')
<script>
  $(function() {
    let dtButtons = $.extend(true, [], $.fn.dataTable.defaults.buttons)
    let deleteButtonTrans = 'delete selected'
    let deleteButton = {
      text: deleteButtonTrans,
      url: "{{ route('admin.bookings.mass_destroy') }}",
      className: 'btn-danger',
      action: function(e, dt, node, config) {
        var ids = $.map(dt.rows({
          selected: true
        }).nodes(), function(entry) {
          return $(entry).data('entry-id')
        });
        if (ids.length === 0) {
          alert('zero selected')
          return
        }
        if (confirm('are you sure ?')) {

```

```

        $.ajax({
            headers: {
                'X-CSRF-TOKEN': $('meta[name="csrf-
token"]').attr('content')
            },
            method: 'POST',
            url: config.url,
            data: {
                ids: ids,
                _method: 'DELETE'
            }
        })
        .done(function() {
            location.reload()
        })
    }
}
}
dtButtons.push(deleteButton)
$.extend(true, $.fn.dataTable.defaults, {
    order: [
        [1, 'asc']
    ],
    pageLength: 50,
});
$('.datatable-booking:not(.ajaxTable)').DataTable({
    buttons: dtButtons
})
$('a[data-toggle="tab"]').on('shown.bs.tab', function(e) {
    ($.fn.dataTable.tables(true)).DataTable()
        .columns.adjust();
});
})
</script>
@endpush

```

View Admin Booking Show

```

@extends('layouts.admin')

@section('content')
<div class="container-fluid">

    <!-- Page Heading -->

    <!-- Content Row -->
    <div class="card">
        <div class="card-header py-3 d-flex">
            <h6 class="m-0 font-weight-bold text-primary">

```

```

        {{ __( 'view booking' ) }}
    </h6>
</div>
<div class="card-body">
    <div class="table-responsive">
        <table class="table table-bordered table-striped table-hover"
cellspacing="0" width="100%">
            <tr>
                <th>Customer Email</th>
                <td>{{ $booking->user->email }}</td>
            </tr>
            <tr>
                <th>Destination</th>
                <td>{{ $booking->package->destination }}</td>
            </tr>
            <tr>
                <th>Price</th>
                <td>Rp&nbsp;{{ number_format($booking->package->price, 0,
',, '.') }}</td>
            </tr>
            <tr>
                <th>Status</th>
                <td>{{ $booking->transaction_status }}</td>
            </tr>
            <tr>
                <th>Sub-Total</th>
                <td>Rp&nbsp;{{ number_format($booking->transaction_total, 0,
',, '.') }}</td>
            </tr>
            <tr>
                <th>Data Pengunjung</th>
                <td>
                    <table class="table table-bordered">
                        <tr>
                            <th>Nama Lengkap</th>
                            <th>Tanggal Lahir</th>
                            <th>Email</th>
                            <th>Nomor Telpon</th>
                            <th>Kewarganegaraan</th>
                        </tr>
                        <tr>
                            @foreach ($booking->details as $detail)
                                <tr>
                                    <td>{{ $detail->nama_lengkap }}</td>
                                    <td>{{ \Carbon\Carbon::parse($detail->tanggal_lahir)-
>translatedFormat('d F Y') }}</td>
                                    <td>{{ $detail->email }}</td>
                                    <td>{{ $detail->numberphone }}</td>
                                    <td>{{ $detail->kewarganegaraan }}</td>
                                </tr>
                            </tr>
                        </tr>
                    </table>
                </td>
            </tr>
        </table>
    </div>
</div>

```

```

        @endforeach
      </table>
    </td>
  </tr>
</table>
</div>
</div>
</div>
<!-- Content Row -->

</div>
@endsection

```

View Admin Categories Create

```

@extends('layouts.admin')

@section('content')
<div class="container-fluid">

  @if($errors->any())
    <div class="alert alert-danger">
      <ul>
        @foreach($errors->all() as $error)
          <li>{{ $error }}</li>
        @endforeach
      </ul>
    </div>
  @endif

  <!-- Content Row -->
  <div class="card shadow">
    <div class="card-header py-3 d-flex">
      <h1 class="h3 mb-0 text-gray-800">{{ __('create category') }}</h1>
      <div class="ml-auto">
        <a href="{{ route('admin.categories.index') }}" class="btn btn-
primary">
          <span class="text">{{ __('Go Back') }}</span>
        </a>
      </div>
    </div>
    <div class="card-body">
      <form action="{{ route('admin.categories.store') }}"
method="POST">
        @csrf
        <div class="form-group">
          <label for="name">{{ __('Name') }}</label>
          <input type="text" class="form-control" id="name"
placeholder="{{ __('name') }}" name="name" value="{{ old('name') }}" />
        </div>

```

```

        <button type="submit" class="btn btn-primary btn-block">{{
__('Save') }}</button>
    </form>
</div>
</div>

<!-- Content Row -->

</div>
@endsection

```

View Admin Categories Edit

```

@extends('layouts.admin')

@section('content')
<div class="container-fluid">

    @if($errors->any())
        <div class="alert alert-danger">
            <ul>
                @foreach($errors->all() as $error)
                    <li>{{ $error }}</li>
                @endforeach
            </ul>
        </div>
    @endif

<!-- Content Row -->
    <div class="card shadow">
        <div class="card-header py-3 d-flex">
            <h1 class="h3 mb-0 text-gray-800">{{ __('create category') }}</h1>
            <div class="ml-auto">
                <a href="{{ route('admin.categories.index') }}" class="btn btn-
primary">
                    <span class="text">{{ __('Go Back') }}</span>
                </a>
            </div>
        </div>
        <div class="card-body">
            <form action="{{ route('admin.categories.update', $category->id) }}"
method="POST">
                @csrf
                @method('put')
                <div class="form-group">
                    <label for="name">{{ __('Name') }}</label>
                    <input type="text" class="form-control" id="name" placeholder="{{
__('name') }}" name="name" value="{{ old('name', $category->name) }}" />
                </div>

```

```

        <button type="submit" class="btn btn-primary btn-block">{{ __('Save')
    }}</button>
    </form>
  </div>
</div>

<!-- Content Row -->

</div>
@endsection

```

View Admin Categories Index

```

@extends('layouts.admin')

@section('content')
  <div class="container-fluid">

    <!-- Page Heading -->

    <!-- Content Row -->
    <div class="card">
      <div class="card-header py-3 d-flex">
        <h6 class="m-0 font-weight-bold text-primary">
          {{ __('category') }}
        </h6>
        <div class="ml-auto">
          <a href="{{ route('admin.categories.create') }}" class="btn btn-
primary">
            <span class="icon text-white-50">
              <i class="fa fa-plus"></i>
            </span>
            <span class="text">{{ __('New category') }}</span>
          </a>
        </div>
      </div>
      <div class="card-body">
        <div class="table-responsive">
          <table class="table table-bordered table-striped table-hover datatable
datatable-Category"
            cellspacing="0" width="100%">
            <thead>
              <tr>
                <th width="10">

                </th>
                <th>No</th>
                <th>Name</th>

```



```

        <th>Action</th>
    </tr>
</thead>
<tbody>
    @forelse($categories as $category)
        <tr data-entry-id="{{ $category->id }}">
            <td>

                </td>
                <td>{{ $loop->iteration }}</td>
                <td>{{ $category->name }}</td>
                <td>
                    <a href="{{ route('admin.categories.edit', $category->id)
}}}" class="btn btn-info">
                        <i class="fa fa-pencil-alt"></i>
                    </a>
                    <form onclick="return confirm('are you sure ? ')"
class="d-inline"
                        action="{{ route('admin.categories.destroy',
$category->id) }}" method="POST">
                        @csrf
                        @method('delete')
                        <button class="btn btn-danger">
                            <i class="fa fa-trash"></i>
                        </button>
                    </form>
                </td>
            </tr>
            @empty
                <tr>
                    <td colspan="7" class="text-center">{{ __('Data Empty')
}}</td>
                </tr>
            @endforelse
        </tbody>
    </table>
</div>
</div>
<!-- Content Row -->

</div>
@endsection

@push('script-alt')
<script>
    $(function() {
        let dtButtons = $.extend(true, [], $.fn.dataTable.defaults.buttons)
        let deleteButtonTrans = 'delete selected'
        let deleteButton = {

```

```

text: deleteButtonTrans,
url: "{{ route('admin.categories.mass_destroy') }}",
className: 'btn-danger',
action: function(e, dt, node, config) {
  var ids = $.map(dt.rows({
    selected: true
  }).nodes(), function(entry) {
    return $(entry).data('entry-id')
  });
  if (ids.length === 0) {
    alert('zero selected')
    return
  }
  if (confirm('are you sure ?')) {
    $.ajax({
      headers: {
        'X-CSRF-TOKEN': $('meta[name="csrf-
token"]').attr('content')
      },
      method: 'POST',
      url: config.url,
      data: {
        ids: ids,
        _method: 'DELETE'
      }
    })
    .done(function() {
      location.reload()
    })
  }
}
}
dtButtons.push(deleteButton)
$.extend(true, $.fn.dataTable.defaults, {
  order: [
    [1, 'asc']
  ],
  pageLength: 50,
});
$('.datatable-Category:not(.ajaxTable)').DataTable({
  buttons: dtButtons
})
$('a[data-toggle="tab"]').on('shown.bs.tab', function(e) {
  $($.fn.dataTable.tables(true)).DataTable()
  .columns.adjust();
});
})
</script>
@endpush

```

View Admin Countries Create

```

@extends('layouts.admin')

@section('content')
<div class="container-fluid">

    @if($errors->any())
        <div class="alert alert-danger">
            <ul>
                @foreach($errors->all() as $error)
                    <li>{{ $error }}</li>
                @endforeach
            </ul>
        </div>
    @endif

<!-- Content Row -->
    <div class="card shadow">
        <div class="card-header py-3 d-flex">
            <h1 class="h3 mb-0 text-gray-800">{{ __('create country') }}</h1>
            <div class="ml-auto">
                <a href="{{ route('admin.countries.index') }}" class="btn btn-primary">
                    <span class="text">{{ __('Go Back') }}</span>
                </a>
            </div>
        </div>
        <div class="card-body">
            <form action="{{ route('admin.countries.store') }}" method="POST">
                @csrf
                <div class="form-group">
                    <label for="name">{{ __('Name') }}</label>
                    <input type="text" class="form-control" id="name" placeholder="{{
__('name') }}" name="name" value="{{ old('name') }}" />
                </div>
                <div class="form-group">
                    <label for="shortcode">{{ __('Short Code') }}</label>
                    <input type="text" class="form-control" id="shortcode"
placeholder="{{ __('shortcode') }}" name="shortcode" value="{{ old('shortcode') }}"
/>
                </div>
                <button type="submit" class="btn btn-primary btn-block">{{ __('Save')
}}</button>
            </form>
        </div>
    </div>

<!-- Content Row -->

```

```

</div>
@endsection

```

View Admin Countries Edit

```

@extends('layouts.admin')

@section('content')
<div class="container-fluid">

    @if($errors->any())
        <div class="alert alert-danger">
            <ul>
                @foreach($errors->all() as $error)
                    <li>{{ $error }}</li>
                @endforeach
            </ul>
        </div>
    @endif

    <!-- Content Row -->
    <div class="card shadow">
        <div class="card-header py-3 d-flex">
            <h1 class="h3 mb-0 text-gray-800">{{ __('create country') }}</h1>
            <div class="ml-auto">
                <a href="{{ route('admin.countries.index') }}" class="btn btn-primary">
                    <span class="text">{{ __('Go Back') }}</span>
                </a>
            </div>
        </div>
        <div class="card-body">
            <form action="{{ route('admin.countries.update', $country->id) }}"
method="POST">
                @csrf
                @method('put')
                <div class="form-group">
                    <label for="name">{{ __('Name') }}</label>
                    <input type="text" class="form-control" id="name" placeholder="{{
__('name') }}" name="name" value="{{ old('name', $country->name) }}" />
                </div>
                <div class="form-group">
                    <label for="shortcode">{{ __('Short Code') }}</label>
                    <input type="text" class="form-control" id="shortcode"
placeholder="{{ __('shortcode') }}" name="shortcode" value="{{ old('shortcode',
$country->shortcode) }}" />
                </div>
                <button type="submit" class="btn btn-primary btn-block">{{ __('Save')
}}</button>
            </form>
        </div>
    </div>

```

```

</div>

<!-- Content Row -->

</div>
@endsection

```

View Admin Countries Index

```

@extends('layouts.admin')

@section('content')
<div class="container-fluid">

    <!-- Page Heading -->

    <!-- Content Row -->
    <div class="card">
        <div class="card-header py-3 d-flex">
            <h6 class="m-0 font-weight-bold text-primary">
                {{ __('country') }}
            </h6>
            <div class="ml-auto">
                <a href="{{ route('admin.countries.create') }}" class="btn btn-
primary">
                    <span class="icon text-white-50">
                        <i class="fa fa-plus"></i>
                    </span>
                    <span class="text">{{ __('New country') }}</span>
                </a>
            </div>
        </div>
        <div class="card-body">
            <div class="table-responsive">
                <table class="table table-bordered table-striped table-hover datatable
datatable-Country"
                    cellspacing="0" width="100%">
                    <thead>
                        <tr>
                            <th width="10">

                                </th>
                                <th>No</th>
                                <th>Name</th>
                                <th>Short Code</th>
                                <th>Action</th>
                            </tr>
                    </thead>

```

```

  @forelse($countries as $country)
    <tr data-entry-id="{{ $country->id }}">
      <td>

        </td>
        <td>{{ $loop->iteration }}</td>
        <td>{{ $country->name }}</td>
        <td>{{ $country->shortcode }}</td>
        <td>
          <a href="{{ route('admin.countries.edit', $country->id) }}"
class="btn btn-info">
            <i class="fa fa-pencil-alt"></i>
          </a>
          <form onclick="return confirm('are you sure ? ')"
class="d-inline"
            action="{{ route('admin.countries.destroy', $country-
>id) }}" method="POST">
            @csrf
            @method('delete')
            <button class="btn btn-danger">
              <i class="fa fa-trash"></i>
            </button>
          </form>
        </td>
      </tr>
    @empty
      <tr>
        <td colspan="7" class="text-center">{{ __('Data Empty')
}}</td>
      </tr>
    @endforelse
  </tbody>
</table>
</div>
</div>
<!-- Content Row -->

</div>
@endsection

@push('script-alt')
<script>
  $(function() {
    let dtButtons = $.extend(true, [], $.fn.dataTable.defaults.buttons)
    let deleteButtonTrans = 'delete selected'
    let deleteButton = {
      text: deleteButtonTrans,
      url: "{{ route('admin.countries.mass_destroy') }}",

```

```

        className: 'btn-danger',
        action: function(e, dt, node, config) {
            var ids = $.map(dt.rows({
                selected: true
            }).nodes(), function(entry) {
                return $(entry).data('entry-id')
            });
            if (ids.length === 0) {
                alert('zero selected')
                return
            }
            if (confirm('are you sure ?')) {
                $.ajax({
                    headers: {
                        'X-CSRF-TOKEN': $('meta[name="csrf-
token"]').attr('content')
                    },
                    method: 'POST',
                    url: config.url,
                    data: {
                        ids: ids,
                        _method: 'DELETE'
                    }
                })
                .done(function() {
                    location.reload()
                })
            }
        }
    }
    dtButtons.push(deleteButton)
    $.extend(true, $.fn.dataTable.defaults, {
        order: [
            [1, 'asc']
        ],
        pageLength: 50,
    });
    $('datatable-Country:not(.ajaxTable)').DataTable({
        buttons: dtButtons
    })
    $('a[data-toggle="tab"]').on('shown.bs.tab', function(e) {
        $($.fn.dataTable.tables(true)).DataTable()
            .columns.adjust();
    });
})
</script>
@endpush

```

View Admin Gallery Create

```

@extends('layouts.admin')

@section('content')
  <!-- Begin Page Content -->
  <div class="container-fluid">

    <!-- Page Heading -->
    <div class="d-sm-flex align-items-center justify-content-between mb-4">
      <h1 class="h3 mb-0 text-gray-800">Tambah Gallery</h1>
    </div>

    @if ($errors->any())
      <div class="alert alert-danger">
        <ul>
          @foreach ($errors->all() as $error)
            <li>{{ $error }}</li>
          @endforeach
        </ul>
      </div>
    @endif

    <div class="card shadow">
      <div class="card-body">
        <form action="{{ route('admin.gallery.store') }}" method="POST"
enctype="multipart/form-data">
          @csrf
          <div class="form-group">
            <label for="packages">{{ __('Destination') }}</label>
            <select class="form-control" name="packages_id" id="packages">
              @foreach ($packages as $id => $package)
                <option value="{{ $id }}">{{ $package }}</option>
              @endforeach
            </select>
          </div>

          <div class="form-grup mt-2">
            <label for="image">Image</label>
            <input type="file" name="image" class="form-control"
placeholder="Image">
          </div>
          <button type="submit" class="btn btn-primary btn-block mt-5">
            Simpan
          </button>
        </form>
      </div>
    </div>
  </div>
<!-- /.container-fluid -->

```



```
@endsection
```

View Admin Gallery Edit

```
@extends('layouts.admin')

@section('content')
  <!-- Begin Page Content -->
  <div class="container-fluid">

    <!-- Page Heading -->
    <div class="d-sm-flex align-items-center justify-content-between mb-4">
      <h1 class="h3 mb-0 text-gray-800">Edit Gallery</h1>
    </div>

    @if ($errors->any())
      <div class="alert alert-danger">
        <ul>
          @foreach ($errors->all() as $error)
            <li>{{ $error }}</li>
          @endforeach
        </ul>
      </div>
    @endif

    <div class="card shadow">
      <div class="card-body">
        <form action="{{ route('admin.gallery.update', $item->id) }}"
method="POST" enctype="multipart/form-data">
          @method('PUT')
          @csrf

          <div class="form-grup">
            <label for="packages_id">Paket Travel</label>
            <select name="packages_id" class="form-control" required>
              <option value="{{ $item->packages_id }}">Jangan
Diubah</option>
              @foreach ($packages as $package)
                <option value="{{ $package->id }}">
                  {{ $package->destination }}
                </option>
              @endforeach
            </select>
          </div>

          <div class="form-grup mt-2">
            <label for="image">Image</label>
            <input type="file" name="image" class="form-control"
placeholder="Image">
          </div>
        </form>
      </div>
    </div>
  </div>
</section>
```

```

        <button type="submit" class="btn btn-primary btn-block">
            Ubah
        </button>
    </form>
</div>
</div>
</div>
<!-- /.container-fluid -->
@endsection

```

View Admin Gallery Index

```

@extends('layouts.admin')

@section('content')
    <!-- Begin Page Content -->
    <div class="container-fluid">

        <!-- Page Heading -->
        <div class="d-sm-flex align-items-center justify-content-between mb-4">
            <h1 class="h3 mb-0 text-gray-800">Gallery</h1>
            <a href="{{ route('admin.gallery.create') }}" class="d-none d-sm-inline-block btn btn-sm btn-primary shadow-sm">
                <i class="fas fa-plus fa-sm text-white-50"></i> Tambah Gallery
            </a>
        </div>

        <!-- Content Row -->
        <div class="row">
            <div class="card-body">
                <div class="table-responsive">
                    <table class="table table-bordered" id="dataTable" width="100%"
cellspacing="0">
                        <thead>
                            <tr>
                                <th>ID</th>
                                <th>Travel</th>
                                <th>Gambar</th>
                                <th>Action</th>
                            </tr>
                        </thead>
                        <tbody>
                            @forelse($items as $item)
                                <tr>
                                    <td>{{ $item->id }}</td>
                                    <td>{{ $item->packages->destination }}</td>
                                    <td>

```

```

        
    </td>
    <td>
        <a href="{{ route('admin.gallery.edit', $item->id) }}"
class="btn btn-info">
            <i class="fa fa-pencil-alt"></i>
        </a>
        <form action="{{ route('admin.gallery.destroy', $item->id)
}}" method="post"
            class="d-inline">
            @csrf
            @method('delete')
            <button class="btn btn-danger">
                <i class="fa fa-trash"></i>
            </button>
        </form>
    </td>
</tr>
@empty
    <td colspan="7" class="text-center">
        Data Kosong
    </td>
@endforelse
</tbody>
</table>
</div>
</div>
</div>
</div>
<!-- /.container-fluid -->
@endsection

```

View Admin Packages Create

```

@extends('layouts.admin')

@section('content')
    <div class="container-fluid">

        @if ($errors->any())
            <div class="alert alert-danger">
                <ul>
                    @foreach ($errors->all() as $error)
                        <li>{{ $error }}</li>
                    @endforeach
                </ul>
            </div>
        @endif
    </div>

```

```

@endif

<!-- Content Row -->
<div class="card shadow">
  <div class="card-header py-3 d-flex">
    <h1 class="h3 mb-0 text-gray-800">{{ __('create destination') }}</h1>
    <div class="ml-auto">
      <a href="{{ route('admin.packages.index') }}" class="btn btn-
primary">
        <span class="text">{{ __('Go Back') }}</span>
      </a>
    </div>
  </div>
  <div class="card-body">
    <form action="{{ route('admin.packages.store') }}" method="POST">
      @csrf
      <div class="form-group">
        <label for="destination">{{ __('Destinasi') }}</label>
        <input type="text" class="form-control" id="destination"
placeholder="{{ __('nama destinasi') }}"
name="destination" value="{{ old('destination') }}" />
      </div>
      <div class="form-group">
        <label for="location">{{ __('Lokasi') }}</label>
        <input type="text" class="form-control" id="location"
placeholder="{{ __('Lokasi') }}"
name="location" value="{{ old('location') }}" />
      </div>
      <div class="form-group">
        <label for="price">{{ __('Harga') }}</label>
        <input type="number" class="form-control" id="price"
placeholder="{{ __('Harga') }}"
name="price" value="{{ old('price') }}" />
      </div>
      <div class="form-group">
        <label for="date">{{ __('Keberangkatan') }}</label>
        <input type="date" class="form-control" id="date"
placeholder="{{ __('Tanggal Berangkat') }}" name="date"
value="{{ old('date') }}" />
      </div>
      <div class="form-group">
        <label for="duration">{{ __('Durasi') }}</label>
        <input type="number" class="form-control" id="duration"
placeholder="{{ __('Durasi') }}"
name="duration" value="{{ old('duration') }}" />
      </div>
      <div class="form-group">
        <label for="category">{{ __('Kategori') }}</label>
        <select class="form-control" name="category_id" id="category">
          @foreach ($categories as $id => $category)

```

```

        <option value="{{ $id }}">{{ $category }}</option>
    @endforeach
</select>
</div>
<div class="form-group">
    <label for="description">{{ __( 'Description' ) }}</label>
    <input id="description" type="hidden" name="description">
    <trix-editor input="description"></trix-editor>
    {{-- <textarea class="form-control" name="description"
id="descriptioin" placeholder="description" cols="30"
        rows="10">{{ old('description') }}</textarea --}}
    </div>
    <button type="submit" class="btn btn-primary btn-block">{{ __( 'Save' )
}}</button>
</form>
</div>
</div>

<!-- Content Row -->

</div>
<script>
    document.addEventListener('trix-file-accept', (function(e)) {
        e.preventDefault();
    })
</script>
@endsection

```

View Admin Packages Edit

```

@extends('layouts.admin')

@section('content')
    <div class="container-fluid">

        @if ($errors->any())
            <div class="alert alert-danger">
                <ul>
                    @foreach ($errors->all() as $error)
                        <li>{{ $error }}</li>
                    @endforeach
                </ul>
            </div>
        @endif

        <!-- Content Row -->
        <div class="card shadow">
            <div class="card-header py-3 d-flex">
                <h1 class="h3 mb-0 text-gray-800">{{ __( 'Update Package' ) }}</h1>

```

```

<div class="ml-auto">
  <a href="{{ route('admin.packages.index') }}" class="btn btn-
primary">
    <span class="text">{{ __('Go Back') }}</span>
  </a>
</div>
</div>
<div class="card-body">
  <form action="{{ route('admin.packages.update', $package->id) }}"
method="POST">
    @csrf
    @method('put')
    <div class="form-group">
      <label for="destination">{{ __('Destination') }}</label>
      <input type="text" class="form-control" id="destination"
placeholder="{{ __('destination') }}"
name="destination" value="{{ old('destination', $package-
>destination) }}" />
    </div>
    <div class="form-group">
      <label for="location">{{ __('Location') }}</label>
      <input type="text" class="form-control" id="location"
placeholder="{{ __('location') }}"
name="location" value="{{ old('location', $package->location) }}"
/>
    </div>
    <div class="form-group">
      <label for="date">{{ __('Keberangkatan') }}</label>
      <input type="date" class="form-control" id="date"
placeholder="{{ __('Tanggal Berangkat') }}" name="date"
value="{{ old('date') ?? $package->date }}" />
    </div>
    <div class="form-group">
      <label for="price">{{ __('Price') }}</label>
      <input type="number" class="form-control" id="price"
placeholder="{{ __('price') }}"
name="price" value="{{ old('price', $package->price) }}" />
    </div>
    <div class="form-group">
      <label for="duration">{{ __('Durasi (Hari)') }}</label>
      <input type="number" class="form-control" id="duration"
placeholder="{{ __('Durasi') }}"
name="duration" value="{{ old('duration', $package->duration)
}} " />
    </div>
    <div class="form-group">
      <label for="category">{{ __('Category') }}</label>
      <select class="form-control" name="category_id" id="category">
        @foreach ($categories as $id => $category)
          <option {{ $id == $package->category->id ? 'selected' : null }}

```

```

        value="{{ $id }}">{{ $category }}</option>
    @endforeach
</select>
</div>
<div class="form-group">
    <label for="description">{{ __( 'Description' ) }}</label>
    <input id="description" type="hidden" name="description"
        value="{{ old('description', $package->description) }}">
    <trix-editor input="description"></trix-editor>

    {{-- <label for="description">{{ __( 'Description' ) }}</label>
        <textarea          class="form-control"          name="description"
id="description" placeholder="description" cols="30"
        rows="10">{{      old('description',      $package->description)
}}</textarea> --}}
    </div>
    <button type="submit" class="btn btn-primary btn-block">{{ __( 'Save' )
}}</button>
</form>
</div>
</div>

<!-- Content Row -->

</div>
@endsection

```

View Admin Packages Index

```

@extends('layouts.admin')

@section('content')
    <div class="container-fluid">

        <!-- Page Heading -->

        <!-- Content Row -->
        <div class="card">
            <div class="card-header py-3 d-flex">
                <h6 class="m-0 font-weight-bold text-primary">
                    {{ __( 'destination' ) }}
                </h6>
                <div class="ml-auto">
                    <a href="{{ route('admin.packages.create') }}" class="btn btn-
primary">
                        <span class="icon text-white-50">
                            <i class="fa fa-plus"></i>
                        </span>
                    </a>
                </div>
            </div>
        </div>
    </div>

```

```

        <span class="text">{{ __( 'New package' ) }}</span>
    </a>
</div>
</div>
<div class="card-body">
    <div class="table-responsive">
        <table class="table table-bordered table-striped table-hover datatable
datatable-package"
        cellspacing="0" width="100%">
            <thead>
                <tr>
                    <th width="10">

                        </th>
                    <th>ID</th>
                    <th>Nama Destinasi</th>
                    <th>Lokasi</th>
                    <th>Keberangkatan</th>
                    <th>Harga</th>
                    <th>Kategori</th>
                    <th>Action</th>
                </tr>
            </thead>
            <tbody>
                @forelse($packages as $package)
                    <tr data-entry-id="{{ $package->id }}">
                        <td>

                            </td>
                        <td>{{ $loop->iteration }}</td>
                        <td>{{ $package->destination }}</td>
                        <td>{{ $package->location }}</td>
                        <td>{{
                            \Carbon\Carbon::parse($package->date)-
                            >translatedFormat('d F Y') }}</td>
                        <td><sup>RP</sup> {{ number_format($package->price,
0, ',', '.') }}</td>
                        <td>{{ $package->category->name }}</td>
                        <td>
                            <a href="{{ route('admin.packages.show', $package->id)
}}" class="btn btn-info">
                                <i class="fa fa-eye"></i>
                            </a>
                            <a href="{{ route('admin.packages.edit', $package->id)
}}" class="btn btn-info">
                                <i class="fa fa-pencil-alt"></i>
                            </a>
                            <form onclick="return confirm('are you sure ? ')"
class="d-inline"
                                action="{{ route('admin.packages.destroy', $package-
>id) }}" method="POST">

```



```

        @csrf
        @method('delete')
        <button class="btn btn-danger">
          <i class="fa fa-trash"></i>
        </button>
      </form>
    </td>
  </tr>
  @empty
  <tr>
    <td colspan="9" class="text-center">{{ __('Data Empty')
}}</td>
  </tr>
  @endforelse
</tbody>
</table>
</div>
</div>
</div>
<!-- Content Row -->

</div>
@endsection

@push('script-alt')
<script>
  $(function() {
    let dtButtons = $.extend(true, [], $.fn.dataTable.defaults.buttons)
    let deleteButtonTrans = 'delete selected'
    let deleteButton = {
      text: deleteButtonTrans,
      url: "{{ route('admin.packages.mass_destroy') }}",
      className: 'btn-danger',
      action: function(e, dt, node, config) {
        var ids = $.map(dt.rows({
          selected: true
        }).nodes(), function(entry) {
          return $(entry).data('entry-id')
        });
        if (ids.length === 0) {
          alert('zero selected')
          return
        }
        if (confirm('are you sure ?')) {
          $.ajax({
            headers: {
              'X-CSRF-TOKEN': $('meta[name="csrf-
token"]').attr('content')
            },
            method: 'POST',

```

```

        url: config.url,
        data: {
            ids: ids,
            _method: 'DELETE'
        }
    })
    .done(function() {
        location.reload()
    })
}
}
}
dtButtons.push(deleteButton)
$.extend(true, $.fn.dataTable.defaults, {
    order: [
        [1, 'asc']
    ],
    pageLength: 50,
});
$('.datatable-package:not(.ajaxTable)').DataTable({
    buttons: dtButtons
})
$('a[data-toggle="tab"]').on('shown.bs.tab', function(e) {
    $($.fn.dataTable.tables(true)).DataTable()
        .columns.adjust();
});
});
</script>
@endpush

```

View Admin Packages Show

```

@extends('layouts.admin')

@section('content')
<div class="container-fluid">

    <!-- Page Heading -->

    <!-- Content Row -->
    <div class="card">
        <div class="card-header py-3 d-flex">
            <h6 class="m-0 font-weight-bold text-primary">
                {{ __('View Package') }}
            </h6>
        </div>
        <div class="card-body">
            <div class="table-responsive">

```

```

        <table class="table table-bordered table-striped table-hover"
cellspacing="0" width="100%">
        <tr>
            <th>Destination</th>
            <td>{{ $package->destination }}</td>
        </tr>
        <tr>
            <th>Location</th>
            <td>{{ $package->location }}</td>
        </tr>
        <tr>
            <th>description</th>
            <td>{!! $package->description !!}</td>
        </tr>
    </table>
</div>
</div>

<!-- Tab panes -->
<div class="card-header py-3 mt-5 bg-info text-white d-flex">
    <h6 class="m-0 font-weight-bold text-white">
        {{ __( 'View Booking' ) }}
    </h6>
</div>
<div class="card-body">
    <div class="table-responsive">
        <table class="table table-bordered table-striped table-hover datatable
datatable-booking"
        cellspacing="0" width="100%">
            <thead>
                <tr>
                    <th width="10"></th>
                    <th>User</th>
                    <th>Destination</th>
                    <th>duration</th>
                    <th>Price</th>
                </tr>
            </thead>
            <tbody>
                @foreach($groupedBookings as $booking)
                    <!-- <tr data-entry-id="{{ $booking->id }}" -->
                    <td></td>
                    <td field-key='package'>{{ $booking['user'] }}</td>
                    <td field-key='package'>{{ $booking['destination'] }}</td>
                    <td field-key='package'>{{ $booking['duration'] }} Hari</td>
                    <td
                        field-key='package'>Rp
                    </td>
                    <td>
                        number_format($booking['total_price'], 0, ',', '.') </td>
                    </td>
                @can('booking_view')

```

```

}}"
    <a href="{{ route('admin.bookings.show', [$booking->id])
    class="btn btn-xs btn-primary"><i class="fa fa-
eye"></i></a>
    @endcan
    @can('booking_edit')
    <a href="{{ route('admin.bookings.edit', [$booking->id])
}}"
    class="btn btn-xs btn-info"><i class="fa fa-pencil-
alt"></i></a>
    @endcan
    @can('booking_delete')
    <form onclick="return confirm('are you sure ? ')"
class="d-inline"
    action="{{ route('admin.bookings.destroy', $booking-
>id) }}" method="POST">
    @csrf
    @method('delete')
    <button class="btn btn-danger">
    <i class="fa fa-trash"></i>
    </button>
    </form>
    @endcan
    </td>
    </tr>
    @empty
    <tr>
    <td colspan="10">data not found !</td>
    </tr>
    @endforelse
    </tbody>
    </table>
    </div>
    </div>
    <!-- Content Row -->

</div>
@endsection

@push('script-alt')
<script>
    $(function() {
    let dtButtons = $.extend(true, [], $.fn.dataTable.defaults.buttons)
    let deleteButtonTrans = 'delete selected'
    let deleteButton = {
    text: deleteButtonTrans,
    url: "{{ route('admin.bookings.mass_destroy') }}",

```

```

        className: 'btn-danger',
        action: function(e, dt, node, config) {
            var ids = $.map(dt.rows({
                selected: true
            }).nodes(), function(entry) {
                return $(entry).data('entry-id')
            });
            if (ids.length === 0) {
                alert('zero selected')
                return
            }
            if (confirm('are you sure ?')) {
                $.ajax({
                    headers: {
                        'X-CSRF-TOKEN': $('meta[name="csrf-
token"]').attr('content')
                    },
                    method: 'POST',
                    url: config.url,
                    data: {
                        ids: ids,
                        _method: 'DELETE'
                    }
                })
                .done(function() {
                    location.reload()
                })
            }
        }
    }
    dtButtons.push(deleteButton)
    $.extend(true, $.fn.dataTable.defaults, {
        order: [
            [1, 'asc']
        ],
        pageLength: 50,
    });
    $('datatable-booking:not(.ajaxTable)').DataTable({
        buttons: dtButtons
    })
    $('a[data-toggle="tab"]').on('shown.bs.tab', function(e) {
        $($.fn.dataTable.tables(true)).DataTable()
            .columns.adjust();
    });
})
</script>
@endpush

```

View Admin Users Create

```

@extends('layouts.admin')

@section('content')
  <div class="container-fluid">

    <!-- Page Heading -->
    <div class="d-sm-flex align-items-center justify-content-between mb-4">
      <h1 class="h3 mb-0 text-gray-800">{{ __('create user') }}</h1>
      <a href="{{ route('admin.users.index') }}" class="btn btn-primary btn-sm shadow-sm">{{ __('Go Back') }}</a>
    </div>

    @if ($errors->any())
      <div class="alert alert-danger">
        <ul>
          @foreach ($errors->all() as $error)
            <li>{{ $error }}</li>
          @endforeach
        </ul>
      </div>
    @endif

    <!-- Content Row -->
    <div class="card shadow">
      <div class="card-body">
        <form action="{{ route('admin.users.store') }}" method="POST">
          @csrf

          <div class="form-group">
            <label for="email">{{ __('Email') }}</label>
            <input type="email" class="form-control" id="email"
placeholder="{{ __('Email') }}"
name="email" value="{{ old('email') }}" />
          </div>
          <div class="form-group">
            <label for="roles">{{ __('Role') }}</label>
            <select name="roles" id="roles" class="form-control select2"
multiple="multiple">
              <option value="ADMIN">Admin</option>
              <option value="USER">User</option>
            </select>
          </div>
          <div class="form-group">
            <label for="password">{{ __('Password') }}</label>
            <input type="password" class="form-control" id="password"
placeholder="{{ __('Password') }}"
name="password" value="{{ old('password') }}" />
          </div>
          <button type="submit" class="btn btn-primary btn-block">{{ __('Save')
}}</button>

```

```

        </form>
      </div>
    </div>

    <!-- Content Row -->

  </div>
@endsection

```

View Admin Users Edit

```

@extends('layouts.admin')

@section('content')
  <div class="container-fluid">

    <!-- Page Heading -->
    <div class="d-sm-flex align-items-center justify-content-between mb-4">
      <h1 class="h3 mb-0 text-gray-800">{{ __('edit user') }}</h1>
      <a href="{{ route('admin.users.index') }}" class="btn btn-primary btn-sm shadow-sm">{{ __('Go Back') }}</a>
    </div>

    @if ($errors->any())
      <div class="alert alert-danger">
        <ul>
          @foreach ($errors->all() as $error)
            <li>{{ $error }}</li>
          @endforeach
        </ul>
      </div>
    @endif

    <!-- Content Row -->
    <div class="card shadow">
      <div class="card-body">
        <form action="{{ route('admin.users.update', $user->id) }}"
method="POST">
          @csrf
          @method('put')
          <div class="form-group">
            <label for="email">{{ __('Email') }}</label>
            <input type="email" class="form-control" id="email"
placeholder="{{ __('Email') }}"
name="email" value="{{ old('email', $user->email) }}" />
          </div>
          <div class="form-group">
            <label for="roles">{{ __('Role') }}</label>

```

```

        <input type="text" class="form-control" id="roles" placeholder="{{
__('Role') }}"
        name="roles" value="{{ old('roles', $user->roles) }}" />
    </div>
    <div class="form-group">
        <label for="password">{{ __('Password') }}</label>
        <input type="password" class="form-control" id="password"
placeholder="{{ __('Password') }}"
        name="password" value="" />
    </div>
</select>
</div>
<button type="submit" class="btn btn-primary btn-block">{{ __('Save')
}}</button>
</form>
</div>
</div>

<!-- Content Row -->

</div>
@endsection

```

View Admin Users Index

```

@extends('layouts.admin')

@section('content')
    <div class="container-fluid">

        <!-- Content Row -->
        <div class="card">
            <div class="card-header py-3 d-flex">
                <h6 class="m-0 font-weight-bold text-primary">
                    {{ __('Users') }}
                </h6>
                <div class="ml-auto">
                    <a href="{{ route('admin.users.create') }}"
class="d-none d-sm-inline-block btn btn-sm btn-primary shadow-
sm">
                        <i class="fas fa-plus fa-sm text-white-50"></i> Tambah User
                    </a>
                </div>
            </div>
            <div class="card-body">
                <div class="table-responsive">
                    <table class="table table-bordered table-striped table-hover datatable
datatable-User" cellspacing="0"
width="100%">

```



```

        <thead>
          <tr>
            <th width="10">

                </th>
                <th>No</th>
                <th>{{ __('Email') }}</th>
                <th>{{ __('Roles') }}</th>
                <th>{{ __('Action') }}</th>
          </tr>
        </thead>
        <tbody>
          @forelse($users as $user)
            <tr data-entry-id="{{ $user->id }}">
              <td></td>
              <td>{{ $loop->iteration }}</td>
              <td>{{ $user->email }}</td>
              <td>{{ $user->roles }}</td>
              <td>
                <a href="{{ route('admin.users.edit', $user->id) }}"
class="btn btn-info">
                  <i class="fa fa-pencil-alt"></i>
                </a>
                <form onclick="return confirm('are you sure ? ')"
class="d-inline"
method="POST">
                  action="{{ route('admin.users.destroy', $user->id) }}"
                  @csrf
                  @method('delete')
                  <button class="btn btn-danger">
                    <i class="fa fa-trash"></i>
                  </button>
                </form>
              </td>
            </tr>
          @empty
            <tr>
              <td colspan="7" class="text-center">{{ __('Data Empty')
}}</td>
            </tr>
          @endforelse
        </tbody>
      </table>
    </div>
  </div>
  <!-- Content Row -->
</div>
@endsection

```

```

@push('script-alt')
<script>
  $(function() {
    let dtButtons = $.extend(true, [], $.fn.dataTable.defaults.buttons)
    let deleteButtonTrans = 'delete selected'
    let deleteButton = {
      text: deleteButtonTrans,
      url: "{{ route('admin.users.mass_destroy') }}",
      className: 'btn-danger',
      action: function(e, dt, node, config) {
        var ids = $.map(dt.rows({
          selected: true
        }).nodes(), function(entry) {
          return $(entry).data('entry-id')
        });
        if (ids.length === 0) {
          alert('zero selected')
          return
        }
        if (confirm('are you sure ?')) {
          $.ajax({
            headers: {
              'X-CSRF-TOKEN': $('meta[name="csrf-
token"]').attr('content')
            },
            method: 'POST',
            url: config.url,
            data: {
              ids: ids,
              _method: 'DELETE'
            }
          })
          .done(function() {
            location.reload()
          })
        }
      }
    }
    dtButtons.push(deleteButton)
    $.extend(true, $.fn.dataTable.defaults, {
      order: [
        [1, 'asc']
      ],
      pageLength: 50,
    });
    $('#datatable-User:not(.ajaxTable)').DataTable({
      buttons: dtButtons
    })
  })

```



```

        <div class="text-xs font-weight-bold text-success text-
uppercase mb-1">
            Balance</div>
        <div class="h5 mb-0 font-weight-bold text-gray-800">{{
$totalTransaction }}</div>
    </div>
    <div class="col-auto">
        <i class="fas fa-dollar-sign fa-2x text-gray-300"></i>
    </div>
</div>
</div>
</div>
</div>
</div>
</div>
<!-- Earnings (Monthly) Card Example -->
<div class="col-xl-3 col-md-4 mb-4">
    <div class="card border-left-info shadow h-100 py-2">
        <div class="card-body">
            <div class="row no-gutters align-items-center">
                <div class="col mr-2">
                    <div class="text-xs font-weight-bold text-info text-uppercase
mb-1">Pending
                </div>
                <div class="row no-gutters align-items-center">
                    <div class="col-auto">
                        <div class="h5 mb-0 mr-3 font-weight-bold text-gray-
800">{{ $pendingStatusCount }}
                    </div>
                </div>
            </div>
        </div>
        <div class="col-auto">
            <i class="fas fa-spinner fa-2x text-gray-300"></i>
        </div>
    </div>
</div>
</div>
</div>
</div>
<!-- Pending Requests Card Example -->
<div class="col-xl-3 col-md-4 mb-4">
    <div class="card border-left-warning shadow h-100 py-2">
        <div class="card-body">
            <div class="row no-gutters align-items-center">
                <div class="col mr-2">
                    <div class="text-xs font-weight-bold text-warning text-
uppercase mb-1">
                        Success</div>
                    <div class="h5 mb-0 font-weight-bold text-gray-800">{{
$successStatusCount }}</div>

```

```

        </div>
        <div class="col-auto">
          <i class="fas fa-check fa-2x text-gray-300"></i>
        </div>
      </div>
    </div>
  </div>
</div>
<!-- Content Row -->

</div>
@endsection

```

View Auth Login

```

@extends('layouts.app')
@section('title', 'Fiyas Tour & Travel | Login')

@section('content')
  <section class="bg-light py-3 py-md-5">
    <div class="container">
      <div class="row justify-content-center">
        <div class="col-12 col-sm-10 col-md-8 col-lg-6 col-xl-5 col-xxl-4">
          <div class="card border border-light-subtle rounded-3 shadow-sm">
            <div class="card-body p-3 p-md-4 p-xl-5">
              <div class="text-center mb-3">
                <a href="#">
                  
                </a>
              </div>
              <h2 class="text-center text-secondary mb-4">log In</h2>
              <form method="POST" action="{{ route('login') }}">
                @csrf
                <div class="row gy-2 overflow-hidden">
                  <div class="col-12">
                    <div class="form-floating mb-3">
                      <input type="email" class="form-control
@error('email') is-invalid @enderror"
                      name="email" id="email"
placeholder="name@example.com"
                      value="{{ old('email') }}" required>
                    </div>
                    @error('email')
                      <span class="invalid-feedback" role="alert">
                        <strong>{{ $message }}</strong>
                      </span>
                    </div>

```

```

        @enderror
        <label for="email" class="form-label">Email</label>
    </div>
</div>
<div class="col-12">
    <div class="form-floating mb-3">
        <input type="password"
            class="form-control @error('password') is-invalid
@enderror" name="password"
            id="password" value="{{ old('email') }}"
placeholder="Password" required>

        @error('password')
            <span class="invalid-feedback" role="alert">
                <strong>{{ $message }}</strong>
            </span>
        @enderror
        <label for="password" class="form-
label">Password</label>
    </div>
</div>
<div class="col-12">
    <div class="d-flex gap-2 justify-content-between">
        <div class="form-check">
            <input class="form-check-input" type="checkbox"
value=""
            name="remember" id="remember" {{
old('remember') ? 'checked' : '' }}>
            <label class="form-check-label text-secondary"
for="rememberMe">
                Keep me logged in
            </label>
        </div>
        @if (Route::has('password.request'))
            <a class="link-primary text-decoration-none"
                href="{{ route('password.request') }}">
                {{ __('Forgot Your Password?') }}
            </a>
        @endif
    </div>
</div>
<div class="col-12">
    <div class="d-grid my-3">
        <button class="btn btn-primary btn-lg"
type="submit">Log in</button>
    </div>
</div>
</div class="col-12">

```

```

        <p class="m-0 text-secondary text-center">Don't have
an account? <a
        href="{{ route('register') }}"
        class="link-primary
        text-decoration-
none">Register</a></p>
    </div>
</div>
</form>
</div>
</div>
</div>
</div>
</div>
</div>
</section>

{{-- <div class="container">
    <div class="row justify-content-center">
        <div class="col-md-8">
            <div class="card">
                <div class="card-header">{{ __('Login') }}</div>

                <div class="card-body">
                    <form method="POST" action="{{ route('login') }}">
                        @csrf

                        <div class="row mb-3">
                            <label for="email"
                                class="col-md-4 col-form-label text-md-end">{{ __('Email
Address') }}</label>

                            <div class="col-md-6">
                                <input id="email" type="email"
                                class="form-control @error('email') is-invalid @enderror"
                                name="email"
                                value="{{ old('email') }}" required autocomplete="email"
                                autofocus>

                                @error('email')
                                    <span class="invalid-feedback" role="alert">
                                        <strong>{{ $message }}</strong>
                                    </span>
                                @enderror
                            </div>
                        </div>

                        <div class="row mb-3">
                            <label for="password"
                                class="col-md-4 col-form-label
                                text-md-end">{{
__('Password') }}</label>

```

```

        <div class="col-md-6">
            <input id="password" type="password"
                class="form-control @error('password') is-invalid
@enderror" name="password"
                required autocomplete="current-password">

            @error('password')
            <span class="invalid-feedback" role="alert">
                <strong>{{ $message }}</strong>
            </span>
            @enderror
        </div>
    </div>

    <div class="row mb-3">
        <div class="col-md-6 offset-md-4">
            <div class="form-check">
                <input class="form-check-input" type="checkbox"
name="remember" id="remember"
                {{ old('remember') ? 'checked' : '' }}>

                <label class="form-check-label" for="remember">
                    {{ __('Remember Me') }}
                </label>
            </div>
        </div>
    </div>

    <div class="row mb-0">
        <div class="col-md-8 offset-md-4">
            <button type="submit" class="btn btn-primary">
                {{ __('Login') }}
            </button>

            @if (Route::has('password.request'))
                <a class="btn btn-link" href="{{ route('password.request')
}}">
                    {{ __('Forgot Your Password?') }}
                </a>
            @endif
        </div>
    </div>
</form>
</div>
</div>
</div>
</div> --}}
@endsection

```


View Auth Register

```

@extends('layouts.app')
@section('title', 'Fiyas Tour & Travel | Register')
@section('content')
    <!-- Login 13 - Bootstrap Brain Component -->
    <section class="bg-light py-3 py-md-5">
        <div class="container">
            <div class="row justify-content-center">
                <div class="col-12 col-sm-10 col-md-8 col-lg-6 col-xl-5 col-xxl-4">
                    <div class="card border border-light-subtle rounded-3 shadow-sm">
                        <div class="card-body p-3 p-md-4 p-xl-5">
                            <div class="text-center mb-3">
                                <a href="#">
                                    
                                </a>
                            </div>
                            <h2 class="text-center text-secondary mb-4">{{ __('Register')
}}</h2>
                            <form method="POST" action="{{ route('register') }}">
                                @csrf

                                <div class="row gy-2 overflow-hidden">
                                    <div class="col-12">
                                        <div class="form-floating mb-3">
                                            <input type="email" class="form-control
@error('email') is-invalid @enderror"
                                                name="email" id="email"
placeholder="name@example.com"
                                                value="{{ old('email') }}" required>

                                            @error('email')
                                                <span class="invalid-feedback" role="alert">
                                                    <strong>{{ $message }}</strong>
                                                </span>
                                            @enderror
                                            <label for="email" class="form-label">{{ __('Email')
}}</label>

                                        </div>
                                    </div>

                                    <div class="col-12">
                                        <div class="form-floating mb-3">
                                            <input type="password"
                                                class="form-control @error('password') is-invalid
@enderror" name="password"
                                                id="password" value="{{ old('password') }}"
placeholder="Password"

```

```

        required>
        @error('password')
        <span class="invalid-feedback" role="alert">
        <strong>{{ $message }}</strong>
        </span>
        @enderror
        <label for="password" class="form-label">{{
__('Password') }}</label>
        </div>
    </div>
    <div class="col-12">
        <div class="d-grid my-3">
            <button class="btn btn-primary btn-lg"
                type="submit">{{ __('Register') }}</button>
        </div>
        <div class="col-12">
            <p class="m-0 text-secondary text-center">You Have
Account? <a
                href="{{ route('login') }}"
                class="link-primary text-decoration-none">Log
In</a></p>
        </div>
    </div>
</div>
</form>
</div>
</div>
</div>
</div>
</div>
</div>
</section>
@endsection

```

View Auth Verify

```

@extends('layouts.app')

@section('content')
    <div class="container">
        <div class="row justify-content-center">
            <div class="col-md-8">
                <div class="card">
                    <div class="card-header">{{ __('Verifikasi Alamat Email Kamu')
}}</div>

                    <div class="card-body">
                        @if (session('resent'))
                            <div class="alert alert-success" role="alert">

```

```

        {{ __('Tautan verifikasi baru telah dikirim ke alamat email
Anda.') }}
    </div>
@endif

    {{ __('Sebelum melanjutkan, silakan periksa email Anda untuk
tautan verifikasi.') }}
    {{ __('Jika Anda tidak menerima email') }},
    <form class="d-inline" method="POST" action="{{
route('verification.resend') }}">
        @csrf
        <button type="submit"
            class="btn btn-link p-0 m-0 align-baseline">{{ __('klik di sini
untuk meminta yang lain') }}</button>.
    </form>
</div>
</div>
</div>
</div>
</div>
@endsection

```

View Email Transaction-Success

```

<!doctype html>
<html xmlns="http://www.w3.org/1999/xhtml" xmlns:v="urn:schemas-microsoft-
com:VML"
    xmlns:o="urn:schemas-microsoft-com:office:office">

<head>
    <title>E-Ticket Confirmation</title>
    <meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1">
    <style type="text/css">
        body {
            margin: 0;
            padding: 0;
            font-family: Arial, sans-serif;
            background-color: #f4f4f4;
        }

        .container {
            max-width: 600px;
            margin: 20px auto;
            background: #ffffff;
            padding: 20px;
            border-radius: 8px;
            box-shadow: 0 0 10px rgba(0, 0, 0, 0.1);
        }
    </style>

```

```

.header {
  text-align: center;
  padding-bottom: 20px;
}

.header img {
  width: 100px;
}

.content {
  font-size: 16px;
  line-height: 24px;
  color: #333;
}

.footer {
  text-align: center;
  font-size: 14px;
  color: #999;
  padding-top: 20px;
}

.button {
  display: block;
  width: max-content;
  background: #0056b3;
  padding: 10px 20px;
  text-align: center;
  color: white;
  text-decoration: none;
  border-radius: 5px;
  margin: 20px auto;
}
</style>
</head>

<body>
  <div class="container">
    <div class="header">
      
    </div>
    <div class="content">
      <h1>Don't Forget Your E-Ticket!</h1>
      <p>Hi, {{ $data->user->name }},</p>
      <p>Your digital ticket has been successfully printed.</p>
      <p><strong>Booking ID: {{ $order_id }}</strong></p>
      <h2>Travel Details</h2>
      <p><strong>Departure:</strong> {{ $data->package->destination }}</p>
      <p><strong>Date and Time:</strong> {{ $data->package->date }}</p>
      <h2>Detail Penumpang</h2>

```

```

<table style="width:100%; border-collapse: collapse; border: 1px solid
#ccc;">
  <tr style="background-color: #f2f2f2; text-align: center;">
    <th>Nama</th>
    <th>Tanggal Lahir</th>
    <th>Kewarganegaraan</th>
  </tr>
  @foreach ($data->details as $detail)
    <tr style="text-align: center;">
      <td style="border: 1px solid #ccc;">{{ $detail->nama_lengkap
}}</td>
      <td style="border: 1px solid #ccc;">{{ $detail->tanggal_lahir }}</td>
      <td style="border: 1px solid #ccc;">{{ $detail->numberphone
}}</td>
      <td style="border: 1px solid #ccc;">{{ $detail->kewarganegaraan
}}</td>
    </tr>
  @endforeach
</table>
</div>
<div class="footer">
  <p>Need Help? WhatsApp 0812-5114-9713</p>
  <p>2024 Fiyas Copyright All Rights Reserved.</p>
</div>
</div>
</body>
</html>

```

View Includes Footer

```

<!-- Footer Start -->
<div class="container-fluid bg-dark text-light footer pt-5 mt-5 wow fadeln" data-
wow-delay="0.1s">
  <div class="container py-5">
    <div class="row g-5">
      <div class="col-lg-3 col-md-6">
        <h4 class="text-white mb-3">Company</h4>
        <a class="btn btn-link" href="">About Us</a>
        <a class="btn btn-link" href="">Contact Us</a>
        <a class="btn btn-link" href="">Privacy Policy</a>
        <a class="btn btn-link" href="">Terms & Condition</a>
        <a class="btn btn-link" href="">FAQs & Help</a>
      </div>
      <div class="col-lg-3 col-md-6">
        <h4 class="text-white mb-3">Contact</h4>
        <p class="mb-2"><i class="fa fa-map-marker-alt me-3"></i>Jalan
Abdullah DG Sirua No.
58</p>

```

```

    <p class="mb-2"><i class="fa fa-phone-alt me-3"></i>0813-5507-
6176</p>
    <div class="d-flex pt-2">
      <a class="btn btn-outline-light btn-social" href=""><i class="fab fa-
instagram"></i></a>
      <a class="btn btn-outline-light btn-social" href=""><i class="fab fa-
facebook-f"></i></a>
      <a class="btn btn-outline-light btn-social" href=""><i class="fab fa-
twitter"></i></a>

    </div>
  </div>
</div>
</div>
<!-- Footer End -->

<!-- Back to Top -->
<a href="#" class="btn btn-lg btn-primary btn-lg-square back-to-top"><i class="bi
bi-arrow-up"></i></a>

```

View Includes Navbar-Alternate

```

<nav class="row navbar navbar-expand-lg navbar-light bg-white">
  <div class="navbar-nav ml-auto mr-auto mr-sm-auto mr-lg-0 mr-md-auto">
    <a class="navbar-brand" href="/">
      
    </a>
  </div>
  <ul class="navbar-nav mr-auto d-none d-lg-block">
    <li>
      <span class="text-muted">| &nbsp;    Beyond the explorer of the
world</span>
    </li>
  </ul>
</nav>

```

View Includes Navbar

```

<!-- Topbar Start -->
<div class="container-fluid bg-dark px-5 d-none d-lg-block">
  <div class="row gx-0">
    <div class="col-lg-8 text-center text-lg-start mb-2 mb-lg-0">
      <div class="d-inline-flex align-items-center" style="height: 45px;">
        <small class="me-3 text-light"><i class="fa fa-map-marker-alt me-
2"></i>Jalan Abdullah DG Sirua No.
58</small>

```

```

        <small class="me-3 text-light"><i class="fa fa-phone-alt me-
2"></i>0813-5507-6176</small>
    </div>
</div>
<div class="col-lg-4 text-center text-lg-end">
    <div class="d-inline-flex align-items-center" style="height: 45px;">
        <a class="btn btn-sm btn-outline-light btn-sm-square rounded-circle me-
2" href=""><i
            class="fab fa-twitter fw-normal"></i></a>
        <a class="btn btn-sm btn-outline-light btn-sm-square rounded-circle me-
2" href=""><i
            class="fab fa-facebook-f fw-normal"></i></a>
        <a class="btn btn-sm btn-outline-light btn-sm-square rounded-circle me-
2" href=""><i
            class="fab fa-instagram fw-normal"></i></a>
    </div>
</div>
</div>
</div>
<!-- Topbar End -->

<!-- Navbar & Hero Start -->
<div class="container-fluid position-relative p-0">
    <nav class="navbar navbar-expand-lg navbar-light px-4 px-lg-5 py-3 py-lg-0">
        <a href="" class="navbar-brand p-0">
            
        </a>
        <button class="navbar-toggler" type="button" data-bs-toggle="collapse"
data-bs-target="#navbarCollapse">
            <span class="fa fa-bars"></span>
        </button>
        <div class="collapse navbar-collapse" id="navbarCollapse">
            <div class="navbar-nav ms-auto py-0">
                <a href="{{ route('home') }}" class="nav-link {{ request()->is('/') ? 'active'
: " }}">Home</a>
                <a href="{{ route('offer') }}"
                    class="nav-link {{ request()->is('our-offer') ? 'active' : "
}}">Packages</a>
                @auth
                    <a href="{{ route('mytransaction', ['id' => Auth::id()]) }}"
                        class="nav-link {{ request()->is('mytransaction') ? 'active' : " }}">My
Transaction</a>
                @endauth
            </div>
        </div>

        {{-- <a href="" class="btn btn-primary rounded-pill py-2 px-4">Register</a> --
    }}
    @guest

```

```

<!-- Mobile Button -->
<form class="form-inline d-sm-block d-md-none">
  <button class="btn btn-primary rounded-pill py-2 px-4" type="button"
    onclick="event.preventDefault(); location.href='{{ url('login') }}';">
    Login
  </button>
</form>

<!-- Desktop Button -->
<form class="form-inline my-2 my-lg-0 d-none d-md-block">
  <button class="btn btn-primary rounded-pill py-2 px-4" type="button"
    onclick="event.preventDefault(); location.href='{{ url('login') }}';">
    Login
  </button>
</form>
@endguest

@auth
  <!-- Mobile Button -->
  <form class="form-inline d-sm-block d-md-none" action="{{ url('logout') }}"
method="POST">
    @csrf
    <button class="btn btn-primary rounded-pill py-2 px-4" type="submit">
      Login
    </button>
  </form>

  <!-- Desktop Button -->
  <form class="form-inline my-2 my-lg-0 d-none d-md-block" action="{{
url('logout') }}" method="POST">
    @csrf
    <button class="btn btn-primary rounded-pill py-2 px-4" type="submit">
      Log Out
    </button>
  </form>
@endauth
</div>
</nav>

```

View Includes Offer-Style

```

<!-- Google Web Fonts -->
<link rel="preconnect" href="https://fonts.googleapis.com">
<link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
<link
href="https://fonts.googleapis.com/css2?family=Heebo:wght@400;500;600&famil
y=Nunito:wght@600;700;800&display=swap"
rel="stylesheet">
<link href="frontend/fonts/font-awesome.min.css" rel="stylesheet">

```



```

<!-- Icon Font Stylesheet -->
<link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/font-awesome/5.15.3/css/all.min.css">
<link href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.4.1/font/bootstrap-icons.css" rel="stylesheet">

<!-- Libraries Stylesheet -->
<link rel="stylesheet" href="/frontend/lib/animate/animate.min.css" />
<link rel="stylesheet" href="/frontend/lib/owlcarousel/assets/owl.carousel.min.css" />
<link rel="stylesheet" href="/frontend/lib/tempusdominus/css/tempusdominus-bootstrap-4.min.css" />
<link rel="stylesheet" href="/frontend/styles/flexslider.css">

<!-- Customized Bootstrap Stylesheet -->
{{- <link rel="stylesheet" href="/frontend/libraries/bootstrap/css/bootstrap.css" /> -}}
<link rel="stylesheet" href="/frontend/libraries/bootstrap/css/bootstrap.min.css" />

<!-- Template Stylesheet -->
<link rel="stylesheet" href="/frontend/styles/style-offer.css" />

```

View Includes Script

```

<script src="https://code.jquery.com/jquery-3.4.1.min.js"></script>
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.0.0/dist/js/bootstrap.bundle.min.js"></script>
<script src="/frontend/lib/wow/wow.min.js"></script>
<script src="/frontend/lib/easing/easing.min.js"></script>
<script src="/frontend/lib/waypoints/waypoints.min.js"></script>
<script src="/frontend/lib/owlcarousel/owl.carousel.min.js"></script>
<script src="/frontend/lib/tempusdominus/js/moment.min.js"></script>
<script src="/frontend/lib/tempusdominus/js/moment-timezone.min.js"></script>
<script src="/frontend/lib/tempusdominus/js/tempusdominus-bootstrap-4.min.js"></script>
<script src="/frontend/scripts/travel.js"></script>
<script src="/frontend/scripts/jquery.flexslider-min.js"></script>

```

View Includes Style

```

<!-- Google Web Fonts -->
<link rel="preconnect" href="https://fonts.googleapis.com">
<link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
<link href="https://fonts.googleapis.com/css2?family=Heebo:wght@400;500;600&family=Nunito:wght@600;700;800&display=swap"

```

```

    rel="stylesheet">
<link href="frontend/fonts/font-awesome.min.css" rel="stylesheet">

<!-- Icon Font Stylesheet -->
<link      rel="stylesheet"      href="https://cdnjs.cloudflare.com/ajax/libs/font-
awesome/5.15.3/css/all.min.css">
<link      href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.4.1/font/bootstrap-
icons.css" rel="stylesheet">

<!-- Libraries Stylesheet -->
<link rel="stylesheet" href="/frontend/lib/animate/animate.min.css" />
<link rel="stylesheet" href="/frontend/lib/owlcarousel/assets/owl.carousel.min.css"
/>
<link rel="stylesheet" href="/frontend/lib/tempusdominus/css/tempusdominus-
bootstrap-4.min.css" />
<link rel="stylesheet" href="/frontend/styles/flexslider.css">

<!-- Customized Bootstrap Stylesheet -->
{{-- <link rel="stylesheet" href="/frontend/libraries/bootstrap/css/bootstrap.css" /> -
-}}
<link rel="stylesheet" href="/frontend/libraries/bootstrap/css/bootstrap.min.css" />

<!-- Template Stylesheet -->
<link rel="stylesheet" href="/frontend/styles/style2.css" />

```

View Includes Transaction-Style

```

<!-- Google Web Fonts -->
<link rel="preconnect" href="https://fonts.googleapis.com">
<link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
<link
href="https://fonts.googleapis.com/css2?family=Heebo:wght@400;500;600&famil
y=Nunito:wght@600;700;800&display=swap"
rel="stylesheet">
<link href="frontend/fonts/font-awesome.min.css" rel="stylesheet">

<!-- Icon Font Stylesheet -->
<link      rel="stylesheet"      href="https://cdnjs.cloudflare.com/ajax/libs/font-
awesome/5.15.3/css/all.min.css">
<link      href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.4.1/font/bootstrap-
icons.css" rel="stylesheet">

<!-- Libraries Stylesheet -->
<link rel="stylesheet" href="/frontend/lib/animate/animate.min.css" />
<link rel="stylesheet" href="/frontend/lib/owlcarousel/assets/owl.carousel.min.css"
/>
<link rel="stylesheet" href="/frontend/lib/tempusdominus/css/tempusdominus-
bootstrap-4.min.css" />
<link rel="stylesheet" href="/frontend/styles/flexslider.css">

```

```

<!-- Customized Bootstrap Stylesheet -->
{{-- <link rel="stylesheet" href="/frontend/libraries/bootstrap/css/bootstrap.css" /> -
-}}
<link rel="stylesheet" href="/frontend/libraries/bootstrap/css/bootstrap.min.css" />

<!-- Template Stylesheet -->
<link rel="stylesheet" href="/frontend/styles/style-transaction.css" />

```

View Layout Admin

```

<!DOCTYPE html>
<html lang="en">

<head>

  <meta charset="utf-8">
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <meta name="viewport" content="width=device-width, initial-scale=1, shrink-to-
fit=no">
  <meta name="description" content="">
  <meta name="author" content="">

  <!-- CSRF Token -->
  <meta name="csrf-token" content="{{ csrf_token() }}">

  <title>Admin Page</title>

  <!-- Custom fonts for this template-->
  <link href="https://cdn.datatables.net/1.10.19/css/jquery.dataTables.min.css"
rel="stylesheet" />
  <link
href="https://cdn.datatables.net/1.10.19/css/dataTables.bootstrap4.min.css"
rel="stylesheet" />
  <link
href="https://cdn.datatables.net/buttons/1.2.4/css/buttons.dataTables.min.css"
rel="stylesheet" />
  <link
href="https://cdn.datatables.net/select/1.3.0/css/select.dataTables.min.css"
rel="stylesheet" />
  <link href="{{ asset('backend/vendor/fontawesome-free/css/all.min.css') }}"
rel="stylesheet" type="text/css">
  <link rel="stylesheet" type="text/css"
href="https://unpkg.com/trix@2.0.0/dist/trix.css">
  <script type="text/javascript"
src="https://unpkg.com/trix@2.0.0/dist/trix.umd.min.js"></script>

  <style>

```

```

    trix-toolbar [data-trix-button-group="file-tools"] {
      display: none;
    }
  </style>

  <link

href="https://fonts.googleapis.com/css?family=Nunito:200,200i,300,300i,400,400i
,600,600i,700,700i,800,800i,900,900i"
  rel="stylesheet">

  <!-- Custom styles for this template-->
  <link href="{{ asset('backend/css/sb-admin-2.min.css') }}" rel="stylesheet">

  @stack('style-alt')
</head>

<body id="page-top">

  <!-- Page Wrapper -->
  <div id="wrapper">

    <!-- Sidebar -->
    @include('partials.sidebar')
    <!-- End of Sidebar -->

    <!-- Content Wrapper -->
    <div id="content-wrapper" class="d-flex flex-column">

      <!-- Main Content -->
      <div id="content">

        <!-- Topbar -->
        <nav class="navbar navbar-expand navbar-light bg-white topbar mb-4
static-top shadow">

          <!-- Sidebar Toggle (Topbar) -->
          <button id="sidebarToggleTop" class="btn btn-link rounded-circle mr-
3">
            <i class="fa fa-bars"></i>
          </button>

          <!-- Topbar Navbar -->
          <ul class="navbar-nav ml-auto">

            <!-- Nav Item - User Information -->
            <li class="nav-item dropdown no-arrow">

```

```

        <a class="nav-link dropdown-toggle" href="#"
id="userDropdown" role="button"
data-toggle="dropdown" aria-haspopup="true" aria-
expanded="false">
        <span
class="mr-2 d-none d-lg-inline text-gray-600 small">{{
auth()->user()->name }}</span>
        
        </a>
        <!-- Dropdown - User Information -->
        <div class="dropdown-menu dropdown-menu-right shadow
animated--grow-in"
aria-labelledby="userDropdown">
        <a class="dropdown-item" href="#"
onclick="event.preventDefault();document.getElementById('logout-
form').submit();">
        <i class="fas fa-sign-out-alt fa-sm fa-fw mr-2 text-gray-
400"></i>
        Logout
        </a>
        <form id="logout-form" action="{{ route('logout') }}"
method="post">
        @csrf
        </form>
        </div>
        </li>
</ul>
</nav>
<!-- End of Topbar -->
@if (session()->has('message'))
<div class="alert alert-{{ session()->get('alert-type') }} alert-
dismissible fade show"
role="alert" id="alert-message">
{{ session()->get('message') }}
<button type="button" class="close" data-dismiss="alert" aria-
label="Close">
<span aria-hidden="true">&times;</span>
</button>
</div>
@endif
<!-- Begin Page Content -->
@yield('content')
<!-- /.container-fluid -->

```

```

</div>
<!-- End of Main Content -->

<!-- Footer -->
<footer class="sticky-footer bg-white">
  <div class="container my-auto">
    <div class="copyright text-center my-auto">
      </div>
    </div>
  </footer>
<!-- End of Footer -->

</div>
<!-- End of Content Wrapper -->

</div>
<!-- End of Page Wrapper -->

<!-- Scroll to Top Button-->
<a class="scroll-to-top rounded" href="#page-top">
  <i class="fas fa-angle-up"></i>
</a>

<!-- Logout Modal-->
<div class="modal fade" id="logoutModal" tabindex="-1" role="dialog" aria-
labelledby="exampleModalLabel"
  aria-hidden="true">
  <div class="modal-dialog" role="document">
    <div class="modal-content">
      <div class="modal-header">
        <h5 class="modal-title" id="exampleModalLabel">Ready to
Leave?</h5>
        <button class="close" type="button" data-dismiss="modal" aria-
label="Close">
          <span aria-hidden="true">x</span>
        </button>
      </div>
      <div class="modal-body">Select "Logout" below if you are ready to end
your current session.</div>
      <div class="modal-footer">
        <form action="" method="POST">
          @csrf
          <button class="btn btn-secondary" type="button" data-
dismiss="modal">Cancel</button>
          <button class="btn btn-primary" type="submit">Logout</button>
        </form>
      </div>
    </div>
  </div>
</div>
</div>
</div>

```

```

<!-- Bootstrap core JavaScript-->
<script src="{{ asset('backend/vendor/jquery/jquery.min.js') }}"></script>
<script src="{{ asset('backend/vendor/bootstrap/js/bootstrap.bundle.min.js')
}}"></script>

<!-- Core plugin JavaScript-->
<script src="{{ asset('backend/vendor/jquery-easing/jquery.easing.min.js')
}}"></script>

<!-- Custom scripts for all pages-->
<script src="{{ asset('backend/js/sb-admin-2.min.js') }}"></script>

<!-- Page level plugins -->
<script src="{{ asset('backend/vendor/chart.js/Chart.min.js') }}"></script>

<script
src="https://cdn.datatables.net/1.10.19/js/jquery.dataTables.min.js"></script>
<script
src="https://cdn.datatables.net/1.10.19/js/dataTables.bootstrap4.min.js"></script
>
<script
src="https://cdn.datatables.net/buttons/1.2.4/js/dataTables.buttons.min.js"></scri
pt>
<script
src="https://cdn.datatables.net/buttons/1.2.4/js/buttons.flash.min.js"></script>
<script
src="https://cdn.datatables.net/buttons/1.2.4/js/buttons.html5.min.js"></script>
<script
src="https://cdn.datatables.net/buttons/1.2.4/js/buttons.print.min.js"></script>
<script
src="https://cdn.rawgit.com/bpampuch/pdfmake/0.1.18/build/pdfmake.min.js"></s
cript>
<script
src="https://cdn.rawgit.com/bpampuch/pdfmake/0.1.18/build/vfs_fonts.js"></scrip
t>
<script
src="https://cdnjs.cloudflare.com/ajax/libs/jszip/2.5.0/jszip.min.js"></script>
<script
src="https://cdn.datatables.net/select/1.3.0/js/dataTables.select.min.js"></script>

<script>
$(function() {
    let copyButtonTrans = 'copy'
    let csvButtonTrans = 'csv'
    let excelButtonTrans = 'excel'
    let pdfButtonTrans = 'pdf'
    let printButtonTrans = 'print'
    let colvisButtonTrans = 'Column visibility'
    let languages = {

```

```

'en': 'https://cdn.datatables.net/plug-ins/1.10.19/i18n/English.json'
};
$.extend(true, $.fn.dataTable.Buttons.defaults.dom.button, {
  className: 'btn'
})
$.extend(true, $.fn.dataTable.defaults, {
  language: {
    url: languages['{{ app()->getLocale() }}']
  },
  columnDefs: [{
    orderable: false,
    className: 'select-checkbox',
    targets: 0
  }, {
    orderable: false,
    searchable: false,
    targets: -1
  }],
  select: {
    style: 'multi+shift',
    selector: 'td:first-child'
  },
  order: [],
  scrollX: true,
  pageLength: 100,
  dom: 'lBfrtip<"actions">',
  buttons: [{
    extend: 'copy',
    className: 'btn-outline-secondary mx-2',
    text: copyButtonTrans,
    exportOptions: {
      columns: ':visible'
    }
  },
  {
    extend: 'csv',
    className: 'btn-outline-secondary mx-2',
    text: csvButtonTrans,
    exportOptions: {
      columns: ':visible'
    }
  },
  {
    extend: 'excel',
    className: 'btn-outline-secondary mx-2',
    text: excelButtonTrans,
    exportOptions: {
      columns: ':visible'
    }
  }
],

```



```

        {
            extend: 'pdf',
            className: 'btn-outline-secondary mx-2',
            text: pdfButtonTrans,
            exportOptions: {
                columns: ':visible'
            }
        },
        {
            extend: 'print',
            className: 'btn-outline-secondary mx-2',
            text: printButtonTrans,
            exportOptions: {
                columns: ':visible'
            }
        },
    ],
    });
    $.fn.dataTable.ext.classes.sPageButton = "";
    });
</script>
@stack('script-alt')
<!-- Page level custom scripts -->
<!-- <script src="{{ asset('backend/js/demo/chart-area-demo.js') }}"></script>
<script src="{{ asset('backend/js/demo/chart-pie-demo.js') }}"></script> -->
<script>
    $(document).ready(function() {
        // Sembunyikan form biaya passport secara default
        $('#passport_fee_section').hide();

        // Tangani perubahan status checkbox
        $('#passport_fee_enabled').change(function() {
            if ($(this).is(':checked')) {
                // Jika checkbox diaktifkan, tampilkan form biaya passport
                $('#passport_fee_section').show();
            } else {
                // Jika checkbox dinonaktifkan, sembunyikan form biaya passport
                $('#passport_fee_section').hide();
            }
        });
    });
</script>
</body>
</html>

```

View Layout App-Pages

```
<!DOCTYPE html>
```

```

<html lang="en">

<head>
  <meta charset="UTF-8" />
  <meta name="viewport" content="width=device-width, initial-scale=1.0" />
  <meta http-equiv="X-UA-Compatible" content="ie=edge" />
  <title>@yield('title')</title>

  @stack('prepend-style')
  @include('includes.style')
  @stack('addon-style')

</head>

<body>
  @include('includes.navbar')
  @yield('content')
  @include('includes.footer')

  @stack('prepend-script')
  @include('includes.script')
  @stack('addon-script')
  <script>
    $(document).ready(function() {
      $('.flexslider').flexslider({
        animation: "slide",
        controlNav: false,
        directionNav: true,
        prevText: '<i class="fas fa-chevron-left"></i>', // FontAwesome left arrow
        nextText: '<i class="fas fa-chevron-right"></i>', // FontAwesome right
        arrow
        slideshowSpeed: 5000,
        animationSpeed: 600,
        smoothHeight: false
      });
    });
  </script>

  <script>
    document.getElementById('search').addEventListener('input', function() {
      let search = this.value;
      if (search.length > 2) {
        fetch(`${ route('ajax-search') }?search=${search}`)
          .then(response => response.json())
          .then(data => {
            let resultsDropdown = document.getElementById('search-results');
            resultsDropdown.innerHTML = "";
            if (data.length > 0) {
              data.forEach(item => {
                let resultItem = document.createElement('a');

```

```

                resultItem.classList.add('dropdown-item');
                resultItem.href = `{{ route('search')
}}?search=${item.destination}`;
                resultItem.textContent = `${item.destination} -
${item.location}`;
                resultsDropdown.appendChild(resultItem);
            });
            resultsDropdown.classList.add('show');
        } else {
            resultsDropdown.classList.remove('show');
        }
    });
} else {
    document.getElementById('search-results').classList.remove('show');
}
});
</script>

<script>
$(document).ready(function() {
    var placeholders = ["Mau Wisata Dalam Negeri?", "Mau Melaksanakan
Umroh?",
    "Cari Destinasi Wisatamu Sekarang!"];
    var index = 0;

    function changePlaceholder() {
        $('#search').attr('placeholder', "");
        var placeholderText = $('#<span class="placeholder-
text"></span>').text(placeholders[index]);
        $('#search').attr('placeholder', placeholderText.text());
        index = (index + 1) % placeholders.length;
    }

    setInterval(changePlaceholder, 2000); // Ganti teks setiap 2 detik
});
</script>

</html>

```

View Layout App

```

<!doctype html>
<html lang="{{ str_replace('_', '-', app()->getLocale()) }}">

<head>
    <meta charset="utf-8">
    <meta name="viewport" content="width=device-width, initial-scale=1">

    <!-- CSRF Token -->

```

```

<meta name="csrf-token" content="{{ csrf_token() }}">

<title>@yield('title')</title>

<!-- Scripts -->
<script src="{{ asset('js/app.js') }}" defer></script>

<!-- Fonts -->
<link rel="dns-prefetch" href="//fonts.gstatic.com">
<link href="https://fonts.googleapis.com/css?family=Nunito" rel="stylesheet">
<!-- Styles -->
<link href="{{ asset('css/app.css') }}" rel="stylesheet">

</head>

<body>
  <main class="py-4">
    @yield('content')
  </main>
</div>
</body>

</html>

```

View Layout Checkout

```

<!DOCTYPE html>
<html lang="en">

<head>
  <meta charset="UTF-8" />
  <meta name="viewport" content="width=device-width, initial-scale=1.0" />
  <meta http-equiv="X-UA-Compatible" content="ie=edge" />
  <title>@yield('title')</title>

  @stack('prepend-style')
  @include('includes.style')
  @stack('addon-style')

</head>

<body>
  {{-- @include('includes.navbar') --}}
  @yield('content')
  @include('includes.footer')

  @stack('prepend-script')
  @include('includes.script')
  @stack('addon-script')
  <script>

```

```

$(document).ready(function() {
  $('.flexslider').flexslider({
    animation: "slide",
    controlNav: false,
    directionNav: true,
    prevText: '<i class="fas fa-chevron-left"></i>', // FontAwesome left arrow
    nextText: '<i class="fas fa-chevron-right"></i>', // FontAwesome right
arrow
    slideshowSpeed: 5000,
    animationSpeed: 600,
    smoothHeight: false
  });
});
</script>
</body>
</html>

```

View Layout Offer Pages

```

<!DOCTYPE html>
<html lang="en">

<head>
  <meta charset="UTF-8" />
  <meta name="viewport" content="width=device-width, initial-scale=1.0" />
  <meta http-equiv="X-UA-Compatible" content="ie=edge" />
  <title>@yield('title')</title>

  @stack('prepend-style')
  @include('includes.offer-style')
  @stack('addon-style')

</head>

<body>
  @include('includes.navbar')
  @yield('content')
  @include('includes.footer')

  @stack('prepend-script')
  @include('includes.script')
  @stack('addon-script')
</body>

</html>

```

View Layout Success

```

<!DOCTYPE html>

```

```

<html lang="en">

<head>
  <meta charset="UTF-8" />
  <meta name="viewport" content="width=device-width, initial-scale=1.0" />
  <meta http-equiv="X-UA-Compatible" content="ie=edge" />
  <title>@yield('title')</title>

  @stack('prepend-style')
  @include('includes.style')
  @stack('addon-style')

</head>

<body>
  <div class="container">
    @include('includes.navbar-alternate')
  </div>

  @yield('content')

  @stack('prepend-script')
  @include('includes.script')
  @stack('addon-script')

</body>

</html>

```

View Layout Transaction-Pages

```

<!DOCTYPE html>
<html lang="en">

<head>
  <meta charset="UTF-8" />
  <meta name="viewport" content="width=device-width, initial-scale=1.0" />
  <meta http-equiv="X-UA-Compatible" content="ie=edge" />
  <title>@yield('title')</title>

  @stack('prepend-style')
  @include('includes.transaction-style')
  @stack('addon-style')

</head>

<body>
  @include('includes.navbar')
  @yield('content')
  @include('includes.footer')

```

```

@stack('prepend-script')
@include('includes.script')
@stack('addon-script')
<script>
  $(document).ready(function() {
    $('.flexslider').flexslider({
      animation: "slide",
      controlNav: false,
      directionNav: true,
      prevText: '<i class="fas fa-chevron-left"></i>', // FontAwesome left arrow
      nextText: '<i class="fas fa-chevron-right"></i>', // FontAwesome right
      arrow
      slideshowSpeed: 5000,
      animationSpeed: 600,
      smoothHeight: false
    });
  });
</script>

<script>
  document.getElementById('search').addEventListener('input', function() {
    let search = this.value;
    if (search.length > 2) {
      fetch(`{{ route('ajax-search') }}?search=${search}`)
        .then(response => response.json())
        .then(data => {
          let resultsDropdown = document.getElementById('search-results');
          resultsDropdown.innerHTML = "";
          if (data.length > 0) {
            data.forEach(item => {
              let resultItem = document.createElement('a');
              resultItem.classList.add('dropdown-item');
              resultItem.href = `{{ route('search') }}?search=${item.destination}`;
              resultItem.textContent = `${item.destination} - ${item.location}`;
              resultsDropdown.appendChild(resultItem);
            });
            resultsDropdown.classList.add('show');
          } else {
            resultsDropdown.classList.remove('show');
          }
        });
    } else {
      document.getElementById('search-results').classList.remove('show');
    }
  });
</script>
</body>

```



```

aria-label="Disabled input example" disabled>
</div>
<table class="table table-responsive-sm text-center">
  <thead>
    <tr>
      <td scope="col">Nama Lengkap</td>
      <td scope="col">Tanggal Lahir</td>
      <td scope="col">Email</td>
      <td scope="col">Nomor Telepon</td>
      <td scope="col">Kewarganegaraan</td>
      <td scope="col"></td>
    </tr>
  </thead>
  <tbody>
    @forelse ($item->details as $detail)
      <tr>
        <td class="align-middle">{{ $detail->nama_lengkap
}}</td>
        <td class="align-middle">{{ $detail->tanggal_lahir
}}</td>
        <td class="align-middle">{{ $detail->email }}</td>
        <td class="align-middle">{{ $detail->numberphone
}}</td>
        <td class="align-middle">{{ $detail->
kewarganegaraan }}</td>
        <td class="align-middle">
          <a href="{{ route('checkout-remove', $detail->id)
}}">
            
          </a>
        </td>
      </tr>
    @empty
      <tr>
        <td colspan="6" class="text-center">
          No Visitor
        </td>
      </tr>
    @endforelse
  </tbody>
</table>
</div>
<div class="member mt-3">
  <h2>Tambah Data Pengunjung</h2>
  <form class="form-row" method="post" action="{{
route('checkout-create', $item->id) }}">
    @csrf

```

```

Name</label>
<label for="nama_lengkap" class="sr-only">Full
invalid @enderror"
<input type="text" name="nama_lengkap"
class="form-control mb-2 @error('nama_lengkap') is-
id="nama_lengkap" placeholder="Full Name" value="{{
old('nama_lengkap') }}" />
@error('nama_lengkap')
<div class="invalid-feedback">{{ $message }}</div>
@enderror

<label for="email" class="sr-only">Email</label>
<input type="text" name="email"
class="form-control mb-2 @error('email') is-invalid
@enderror" id="email"
placeholder="Email" value="{{ old('email') }}" />
@error('email')
<div class="invalid-feedback">{{ $message }}</div>
@enderror

<label for="numberphone" class="sr-only">Email</label>
<input type="text" name="numberphone"
class="form-control mb-2 @error('numberphone') is-
invalid @enderror"
id="numberphone" placeholder="numberphone"
value="{{ old('numberphone') }}" />
@error('numberphone')
<div class="invalid-feedback">{{ $message }}</div>
@enderror

Lahir</label>
<label for="tanggal_lahir" class="sr-only">Tanggal
Lahir</label>
<input type="text" name="tanggal_lahir"
class="form-control datepicker mb-2
@error('tanggal_lahir') is-invalid @enderror"
id="tanggal_lahir" placeholder="Tanggal Lahir"
value="{{ old('tanggal_lahir') }}" />
@error('tanggal_lahir')
<div class="invalid-feedback">{{ $message }}</div>
@enderror

<label for="kewarganegaraan" class="sr-
only">Kewarganegaraan</label>
<select class="form-control mt-2 mb-2
@error('kewarganegaraan') is-invalid @enderror"
name="kewarganegaraan" id="kewarganegaraan">
<option value="">Pilih Kewarganegaraan</option>
@foreach ($countries as $country)

```

```

        <option value="{{ $country->name }}">{{ $country-
>name }}</option>
        @endforeach
    </select>
    @error('kewarganegaraan')
        <div class="invalid-feedback">{{ $message }}</div>
    @enderror

    <button type="submit" class="btn btn-add-now mb-2 px-2
">
        Add Now
    </button>
</form>

</div>
</div>
</div>
<div class="col-lg-4">
    <div class="card card-details card-right">
        <h2>Informasi Pembayaran</h2>
        <table class="trip-informations">
            <tr>
                <th width="50%">Members</th>
                <td width="50%" class="text-right">{{ $item->details-
>count() }} person</td>
            </tr>
            <tr>
                <th width="50%">Trip Price</th>
                <td width="50%" class="text-right">
                    Rp.{{ number_format($item->package->price, 0, '.', '.')
}}/person
            </td>
            </tr>
            <tr>
                <th width="50%">Sub Total</th>
                <td width="50%" class="text-right">
                    @if ($item->transaction_total > 0)
                        Rp.{{ number_format($item->transaction_total
($item->transaction_total - $item->package->price), 0, '.', '.') }}
                    @else
                        Rp.0
                    @endif
            </td>
            </tr>
            <tr>
                <th width="50%">Total (+Unique)</th>
                <td width="50%" class="text-right text-total">
                    <span class="text-blue">Rp.
                        {{ number_format($item->transaction_total, 0, '.', '.')
}}</span>

```

```

        </td>
      </tr>
    </table>

  </div>
  <div class="join-container text-center">
    <a href="{{ route('checkout-success', $item->id) }}"
      class="btn btn-block btn-join-now mt-3 py-2">Process
Payment</a>
  </div>
  <div class="text-center mt-3">
    <a href="{{ route('detail', $item->package->id) }}" class="text-
muted">Cancel
      Booking</a>
  </div>
</div>
</div>
</div>
</section>
</main>
@endsection

@push('prepend-style')
  <link rel="stylesheet" href="/frontend/libraries/gijgo/css/gijgo.min.css" />
@endpush

@push('addon-script')
  <script src="/frontend/libraries/gijgo/js/gijgo.min.js"></script>
  <script>
    $(document).ready(function() {
      $('.datepicker').datepicker({
        format: 'yyyy-mm-dd',
        uiLibrary: 'bootstrap4',
        icons: {
          rightIcon: ''
        }
      });
    });
  </script>
@endpush

```

View Pages Detail

```

@extends('layouts.checkout')

@section('title', 'Detail Page')

@section('content')
  <main>
    <section class="section-details-header"></section>

```

```

<section class="section-details-content">
  <div class="container">
    <div class="row">
      <div class="col p-0 pl-3 pl-lg-0">
        <nav aria-label="breadcrumb">
          <ol class="breadcrumb">
            <li class="breadcrumb-item" aria-current="page">
              Home
            </li>
            <li class="breadcrumb-item active" aria-current="page">
              Packages
            </li>
          </ol>
        </nav>
      </div>
    </div>
    <div class="row">
      <div class="col-lg-7 pl-lg-0">
        <div class="card card-details">
          <h1>{{ $item->destination }}</h1>
          <p>
            {{ $item->location }}
          </p>
          @if ($item->galleries->count())
            <div class="gallery">
              <div class="xzoom-container">
                galleries->first()-
>image) }}" />
                <div class="xzoom-thumbs">
                  @foreach ($item->galleries as $gallery)
                    <a href="{{ Storage::url($gallery->image) }}">image) }}"
                    /></a>
                  @endforeach
                </div>
              </div>
            </div>
          @endif
          <h2>Tentang Wisata</h2>
          <p>
            {!! $item->description !!}
          </p>
        </div>
      </div>
    </div>
  </div>

```

```

<div class="col-lg-5">
  <div class="card card-details card-right">
    <h2>Informasi Perjalanan</h2>
    <table class="trip-informations">
      <tr>
        <th width="50%">Keberangkatan</th>
        <td width="50%" class="text-left">
          {{ \Carbon\Carbon::create($item->departure_date)-
>format('F n, Y') }}
        </td>
      </tr>
      <tr>
        <th width="50%">Durasi</th>
        <td width="50%" class="text-left">{{ $item->duration }}
Hari</td>
      </tr>
      <tr>
        <th width="50%">Harga</th>
        <td width="50%" class="text-left">Rp.
          {{ number_format($item->price, 0, '.', '.') }}/orang
        </td>
      </tr>
    </table>
  </div>
  <div class="join-container text-center">
    @auth
      <form action="{{ route('checkout_process', $item->id) }}"
method="post">
        @csrf
        <button class="btn btn-block btn-join-now mt-3 py-2"
type="submit">
          Checkout
        </button>
      </form>
    @endauth
    @guest
      <a href="{{ route('login') }}" class="btn btn-block btn-join-now
mt-3 py-2">Login or
        Register
        to
        Join</a>
    @endguest
  </div>
</div>
</div>
</section>
</main>
@endsection

```

```

@push('prepend-style')
  <link rel="stylesheet" href="/frontend/libraries/xzoom/dist/xzoom.css" />
@endpush

@push('addon-script')
  <script src="/frontend/libraries/xzoom/dist/xzoom.min.js"></script>
  <script>
    $(document).ready(function() {
      $('.xzoom, .xzoom-gallery').xzoom({
        zoomWidth: 500,
        title: false,
        tint: '#333',
        Xoffset: 15
      });
    });
  </script>
@endpush

```

View Pages Home

```

@extends('layouts.app_pages')

@section('title', 'Home | FIYAS')

@section('content')
  <header>
    <!-- Flexslider -->
    <div class="flexslider">
      <div class="overlay"></div>
      <ul class="slides">
        <li>
          
        </li>
        <li>
          
        </li>
        <li>
          
        </li>
      </ul>
    </div>

    <div class="container-fluid py-5 mb-5">
      <div class="container py-5 hero-header">
        <div class="row justify-content-center py-5">
          <div class="col-lg-10 pt-lg-5 mt-lg-5 text-center">

```

```

        <h1 class="display-3 mb-3 text-white animated
slideDown">FIYAS TOUR & TRAVEL MAKASSAR</h1>
        <p class="fs-4 mb-4 animated text-white slideInDown">Solusi
Perjalanan Wisata Umroh dan
        Domestikmu</p>
        <div class="position-relative w-75 mx-auto animated
slideDown">
            <form action="{{ route('search') }}" method="GET">
                <div class="form-group">
                    <input class="form-control border-0 rounded-pill w-100 py-
3 ps-4 pe-5" id="search"
                        name="search" type="text" placeholder="Cari Destinasi
Wisatamu Sekarang!">
                    <button type="submit"
                        class="btn btn-primary rounded-pill py-2 px-4 position-
absolute top-0 end-0 me-2"
                        style="margin-top: 7px;">Search</button>
                </div>
                <div id="search-results" class="dropdown-menu mt-2"
                    style="width: 100%; background-color: rgba(255, 255, 255,
0.8)"></div>
            </form>
        </div>
    </div>
</div>
</div>
</div>
</div>
</div>
</div>
</div>
<!-- Navbar & Hero End -->
</header>
<main>
    <!-- About Start -->
    <div class="container-xxl py-5">
        <div class="container">
            <div class="row g-5">
                <div class="col-lg-6 wow fadeInUp" data-wow-delay="0.1s"
style="min-height: 400px;">
                    <div class="position-relative h-100">
                        
                    </div>
                </div>
                <div class="col-lg-6 wow fadeInUp" data-wow-delay="0.3s">
                    <h6 class="section-title bg-white text-start text-primary pe-
3">Tentang Kami</h6>
                    <h1 class="mb-4">Selamat Datang di <span class="text-
primary">PT Fiyas Tour & Travel</span></h1>
                    <p class="mb-4">Fiyas Tour & Travel sudah buka sejak tahun
2017.</p>

```



```

        <p class="mb-4">berlokasi di Jalan Abdullah dg sirua Nomor 58,
Manggala masale, Masale, Kec.
        Panakkukang, Kota Makassar, Sulawesi Selatan 90213,
Indonesia.</p>
        <a class="btn btn-primary py-3 px-5 mt-2" href="{{ route('offer')
}}">Read More</a>
        </div>
        </div>
        </div>
        </div>
        <!-- About End -->

        <!-- Package Start -->
        <div class="container-xxl py-5">
        <div class="container">
        <div class="text-center wow fadeInUp" data-wow-delay="0.1s">
        <h6 class="section-title bg-white text-center text-primary px-3">Paket
Wisata</h6>
        <h1 class="mb-5">Paket Wisata Populer</h1>
        </div>
        <div class="row g-4 justify-content-center">
        @foreach ($packages as $item)
        <div class="col-lg-4 col-md-6 wow fadeInUp" data-wow-
delay="0.1s">
        <div class="package-item">
        <div class="overflow-hidden">
        <a href="{{ route('detail', $item->id) }}">
        
        </a>
        </div>
        <div class="d-flex border-bottom">
        <small class="flex-fill text-center border-end py-2"><i
class="fa fa-map-marker-alt text-primary me-2"></i>{{
$item->location }}</small>
        <small class="flex-fill text-center border-end py-2"><i
class="fa fa-calendar-alt text-primary me-2"></i>{{
\Carbon\Carbon::parse($item->date)->translatedFormat('d F Y') }}</small>
        <small class="flex-fill text-center border-end py-2"><i
class="fa fa-clock text-primary me-2"></i>{{ $item-
>duration }} Hari</small>
        </div>
        <div class="text-center p-4">
        <h4 class="mb-0">{{ $item->destination }}</h4>
        <p class="line-clamp">{!! strip_tags(Str::limit($item-
>description, 100)) !!}</p>
        <h4>Rp {{ number_format($item->price, 0, ',', '.') }}</h4>
        <div class="d-flex justify-content-center mb-2">

```

```

        <a href="{{ route('detail', $item->id) }}"
          class="btn btn-sm btn-primary px-3 border-end"
          style="border-radius: 30px 30px 30px 30px;">Read
More</a>
      </div>
    </div>
  </div>
</div>
@endforeach
</div>
</div>
</div>
<!-- Package End -->

<!-- Process Start -->
<div class="container-xxl py-5">
  <div class="container">
    <div class="text-center pb-4 wow fadeInUp" data-wow-delay="0.1s">
      <h6 class="section-title bg-white text-center text-primary px-3">Proses Pemesanan</h6>
      <h1 class="mb-5">3 Langkah Mudah</h1>
    </div>
    <div class="row gy-5 gx-4 justify-content-center">
      <div class="col-lg-4 col-sm-6 text-center pt-4 wow fadeInUp" data-
wow-delay="0.1s">
        <div class="position-relative border border-primary pt-5 pb-4 px-
4">
          <div class="d-inline-flex align-items-center justify-content-center
bg-primary rounded-circle position-absolute top-0 start-50 translate-middle
shadow"
            style="width: 100px; height: 100px;">
            <i class="fa fa-globe fa-3x text-white"></i>
          </div>
          <h5 class="mt-4">Pilih Destinasi</h5>
          <hr class="w-25 mx-auto bg-primary mb-1">
          <hr class="w-50 mx-auto bg-primary mt-0">
          <p class="mb-0">Temukan destinasi impian Anda dengan
mudah. Jelajahi berbagai pilihan
          destinasi yang menakjubkan dan pilih tempat yang sesuai
dengan keinginan Anda untuk
          petualangan yang tak terlupakan.</p>
        </div>
      </div>
    </div>
    <div class="col-lg-4 col-sm-6 text-center pt-4 wow fadeInUp" data-
wow-delay="0.3s">
      <div class="position-relative border border-primary pt-5 pb-4 px-
4">
        <div class="d-inline-flex align-items-center justify-content-center
bg-primary rounded-circle position-absolute top-0 start-50 translate-middle
shadow"

```

```

        style="width: 100px; height: 100px;">
        <i class="fa fa-dollar-sign fa-3x text-white"></i>
    </div>
    <h5 class="mt-4">Melakukan Pembayaran</h5>
    <hr class="w-25 mx-auto bg-primary mb-1">
    <hr class="w-50 mx-auto bg-primary mt-0">
    <p class="mb-0">Setelah memilih destinasi, langkah
selanjutnya adalah melakukan pembayaran
        dengan mudah dan aman. Kami menyediakan berbagai
pilihan metode pembayaran yang fleksibel,
        sehingga Anda dapat melakukan pembayaran dengan
nyaman dan tanpa khawatir.</p>
    </div>
</div>
<div class="col-lg-4 col-sm-6 text-center pt-4 wow fadeInUp" data-
wow-delay="0.5s">
    <div class="position-relative border border-primary pt-5 pb-4 px-
4">
        <div class="d-inline-flex align-items-center justify-content-center
bg-primary rounded-circle position-absolute top-0 start-50 translate-middle
shadow"
            style="width: 100px; height: 100px;">
            <i class="fa fa-plane fa-3x text-white"></i>
        </div>
        <h5 class="mt-4">Berangkat</h5>
        <hr class="w-25 mx-auto bg-primary mb-1">
        <hr class="w-50 mx-auto bg-primary mt-0">
        <p class="mb-0">Semua sudah siap! Saatnya untuk memulai
petualangan Anda. Dengan semua detail
            yang diatur dan pembayaran yang sudah dilakukan, Anda
tinggal menunggu saatnya untuk
            berangkat dan menjelajahi destinasi impian Anda.</p>
    </div>
</div>
</div>
</div>
</div>
<!-- Process Start -->
</main>
@endsection

```

View Pages My Transaction

```

@extends('layouts.transaction_pages')

@section('content')
    <div class="container-fluid">

        <!-- Page Heading -->

```

```

<!-- Content Row -->
<div class="card">
  <div class="card-header py-3 d-flex">
    <h6 class="m-0 font-weight-bold text-primary">
      {{ __('My Transaction') }}
    </h6>
  </div>
  <div class="card-body">
    <div class="table-responsive">
      <table class="table table-bordered table-striped table-hover datatable
datatable-package" cellspacing="0"
width="100%">
        <thead>
          <tr>
            <th width="10">

            </th>
            <th>ID</th>
            <th>Nama Paket</th>
            <th>Lokasi</th>
            <th>Keberangkatan</th>
            <th>Harga</th>
            <th>Status</th>
            <th>Action</th>
          </tr>
        </thead>
        <tbody>
          @forelse($mytransactions as $item)
            <tr data-entry-id="{{ $item->id }}">
              <td>

              </td>
              <td>{{ $loop->iteration }}</td>
              <td>{{ $item->package->destination }}</td>
              <td>{{ $item->package->location }}</td>
              <td>{{ \Carbon\Carbon::parse($item->package->date)-
>translatedFormat('d F Y') }}</td>
              <td><sup>RP</sup>      {{      number_format($item-
>transaction_total, 0, ',', '.') }}</td>
              <td>{{ $item->transaction_status }}</td>
              <td>
                @if ($item->transaction_status == 'PENDING')
                  <a href="{{ route('midtrans.redirect', ['order_id' =>
$item->id, 'snap_token' => $item->snap_token]) }}"
                    class="btn btn-info">
                      {{ __('Bayar Sekarang') }}
                    </a>
                  <a href="{{ route('checkout', ['id' => $item->id]) }}"
class="btn btn-danger">

```

```

                {{ __('Ubah Bank') }}
            </a>
            @elseif ($item->transaction_status == 'IN_CART')
            <a href="{{ route('checkout', ['id' => $item->id]) }}"
class="btn btn-warning">
                {{ __('Lihat Detail') }}
            </a>
            @elseif ($item->transaction_status == 'FAILED')
            <a href="{{ route('checkout', ['id' => $item->id]) }}"
class="btn btn-warning">
                {{ __('Checkout Ulang') }}
            @elseif ($item->transaction_status == 'EXPIRED')
            <a href="{{ route('checkout', ['id' => $item->id]) }}"
            class="btn btn-warning">
                {{ __('Checkout Ulang') }}
            </a>
            @endif
        </td>
    </tr>
    @empty
    <tr>
        <td colspan="9" class="text-center">{{ __('Data Empty')
}}</td>
    </tr>
    @endforelse
</tbody>
</table>
</div>
</div>
</div>
<!-- Content Row -->

</div>
@endsection

@push('script-alt')
<script>
    $(function() {
        let dtButtons = $.extend(true, [], $.fn.dataTable.defaults.buttons)
        let deleteButtonTrans = 'delete selected'
        let deleteButton = {
            text: deleteButtonTrans,
            url: "{{ route('admin.packages.mass_destroy') }}",
            className: 'btn-danger',
            action: function(e, dt, node, config) {
                var ids = $.map(dt.rows({
                    selected: true
                }).nodes(), function(entry) {
                    return $(entry).data('entry-id')
                });
            };
        };
    });

```

```

        if (ids.length === 0) {
            alert('zero selected')
            return
        }
        if (confirm('are you sure ?')) {
            $.ajax({
                headers: {
                    'X-CSRF-TOKEN': $('meta[name="csrf-
token"]').attr('content')
                },
                method: 'POST',
                url: config.url,
                data: {
                    ids: ids,
                    _method: 'DELETE'
                }
            })
            .done(function() {
                location.reload()
            })
        }
    }
}
dtButtons.push(deleteButton)
$.extend(true, $.fn.dataTable.defaults, {
    order: [
        [1, 'desc'] // Mengurutkan berdasarkan kolom ID secara descending
    ],
    pageLength: 50,
});
$('.datatable-package:not(.ajaxTable)').DataTable({
    buttons: dtButtons
})
$('a[data-toggle="tab"]').on('shown.bs.tab', function(e) {
    $($.fn.dataTable.tables(true)).DataTable()
        .columns.adjust();
});
})
</script>
@endpush

```

View Pages Offer

```

@extends('layouts.offer_pages')

@section('title', 'Our Offer')

@section('content')
    <main>
        <div class="container-xxl py-5">

```

```

<div class="container mt-5">
  <div class="text-center wow fadeInUp" data-wow-delay="0.1s">
    <h6 class="section-title bg-white text-center text-primary px-3">Paket
Wisata</h6>
    <h1 class="mb-5">Paket Wisata Populer</h1>
  </div>
  <div class="row g-4 justify-content-center">
    @foreach ($packages as $item)
      <div class="col-lg-4 col-md-6 wow fadeInUp" data-wow-
delay="0.1s">
        <div class="package-item">
          <div class="overflow-hidden">
            
          </div>
          <div class="d-flex border-bottom">
            <small class="flex-fill text-center border-end py-2"><i
class="fa fa-map-marker-alt text-primary me-2"></i>{{
$item->location }}</small>
            <small class="flex-fill text-center border-end py-2"><i
class="fa fa-calendar-alt text-primary me-2"></i>{{
$item->date }}</small>
          </div>
          <div class="text-center p-4">
            <h3 class="mb-0">Rp {{ number_format($item->price, 0, '.',
'.') }}</h3>
            <div class="mb-3">
              <small class="fa fa-star text-primary"></small>
              <small class="fa fa-star text-primary"></small>
              <small class="fa fa-star text-primary"></small>
              <small class="fa fa-star text-primary"></small>
              <small class="fa fa-star text-primary"></small>
            </div>
            <p class="line-clamp">{!! strip_tags(Str::limit($item-
>description, 100)) !!}</p>
            <div class="d-flex justify-content-center mb-2">
              <a href="{{ route('detail', $item->id) }}"
class="btn btn-sm btn-primary px-3 border-end"
style="border-radius: 30px 30px 30px 30px;">Read
More</a>
            </div>
          </div>
        </div>
      </div>
    @endforeach
  </div>
</div>

```

```

<!-- Package End -->

</main>
@endsection

```

View Pages Success

```

@extends('layouts.success')

@section('title', 'Checkout Success')

@section('content')
<main>
  <div class="section-success d-flex align-items-center">
    <div class="col text-center">
      
      <h1>Yay! Success</h1>
      <p>
        We've sent you email for trip instruction

        <br />
        please read it as well
      </p>
      <a href="/" class="btn btn-home-page mt-3 px-5">
        Home Page
      </a>
    </div>
  </div>
</main>
@endsection

```

View Pages Unfinish

```

@extends('layouts.success')

@section('title', 'Checkout Unfinish')

@section('content')
<main>
  <div class="section-success d-flex align-items-center">
    <div class="col text-center">
      <h1>Pembayaran Pending </h1>
      <p>
        Silahkan Lanjutkan Pembayaran
      </p>
      <a href="/" class="btn btn-home-page mt-3 px-5">
        Home Page
      </a>
    </div>
  </div>
</main>

```



```

</main>
@endsection

```

View Pages Failed

```

@extends('layouts.success')

@section('title', 'Checkout Failed')

@section('content')
<main>
  <div class="section-success d-flex align-items-center">
    <div class="col text-center">
      <h1>Oops!</h1>
      <p>
        Your Transaction is failed
        <br />
        please contact our representative if this problem occurs
      </p>
      <a href="/" class="btn btn-home-page mt-3 px-5">
        Home Page
      </a>
    </div>
  </div>
</main>
@endsection

```

View Partial Sidebar

```

<ul class="navbar-nav bg-gradient-primary sidebar sidebar-dark accordion"
id="accordionSidebar">

  <!-- Sidebar - Brand -->
  <a class="sidebar-brand d-flex align-items-center justify-content-center"
href="{{ url('/') }}">
    <div class="sidebar-brand-text mx-3">{{ __('Homepage') }}</div>
  </a>

  <!-- Divider -->
  <hr class="sidebar-divider my-0">

  <li class="nav-item {{ request()->is('admin/dashboard') || request()-
>is('admin/dashboard') ? 'active' : '' }}">
    <a class="nav-link" href="{{ route('admin.dashboard.index') }}">
      <i class="fas fa-fw fa-tachometer-alt"></i>
      <span>{{ __('Dashboard') }}</span></a>
  </li>

  <!-- Divider -->
  <hr class="sidebar-divider">

```

```

<li class="nav-item">
  <a class="nav-link" href="#" data-toggle="collapse" data-
target="#collapseTwo" aria-expanded="true"
aria-controls="collapseTwo">
    <span>{{ __('User Management') }}</span>
  </a>
  <div id="collapseTwo" class="collapse" aria-labelledby="headingTwo" data-
parent="#accordionSidebar">
    <div class="bg-white py-2 collapse-inner rounded">
      <a class="collapse-item {{ request()->is('admin/users') || request()-
>is('admin/users/*') ? 'active' : '' }}"
href="{{ route('admin.users.index') }}"> <i class="fa fa-user mr-2"></i>
{{ __('Users') }}</a>
    </div>
  </div>
</li>

<li class="nav-item">
  <a class="nav-link" href="#" data-toggle="collapse" data-
target="#collapsePackage" aria-expanded="true"
aria-controls="collapseTwo">
    <span>{{ __('Package Management') }}</span>
  </a>
  <div id="collapsePackage" class="collapse" aria-labelledby="headingTwo"
data-parent="#accordionSidebar">
    <div class="bg-white py-2 collapse-inner rounded">
      <a class="collapse-item {{ request()->is('admin/countries') || request()-
>is('admin/countries/*') ? 'active' : '' }}"
href="{{ route('admin.countries.index') }}"> <i class="fa fa-briefcase
mr-2"></i>
      {{ __('country') }}</a>
      <a class="collapse-item {{ request()->is('admin/categories') || request()-
>is('admin/categories/*') ? 'active' : '' }}"
href="{{ route('admin.categories.index') }}"> <i class="fa fa-user mr-
2"></i>
      {{ __('category') }}</a>
      <a class="collapse-item {{ request()->is('admin/packages') || request()-
>is('admin/packages/*') ? 'active' : '' }}"
href="{{ route('admin.packages.index') }}"><i class="fa fa-plane"></i>
      {{ __('destination') }}</a>
      <a class="collapse-item {{ request()->is('admin/gallery') || request()-
>is('admin/gallery/*') ? 'active' : '' }}"
href="{{ route('admin.gallery.index') }}"><i class="fa fa-file-
image"></i>
      {{ __('Gallery') }}</a>
    </div>
  </div>
</li>

```

```

<li class="nav-item">
  <a class="nav-link" href="#" data-toggle="collapse" data-
target="#collapseBooking" aria-expanded="true"
aria-controls="collapseTwo">
    <span>{{ __('Booking Management') }}</span>
  </a>
  <div id="collapseBooking" class="collapse" aria-labelledby="headingTwo"
data-parent="#accordionSidebar">
    <div class="bg-white py-2 collapse-inner rounded">
      <a class="collapse-item {{ request()->is('admin/bookings') || request()-
>is('admin/bookings/*') ? 'active' : '' }}"
href="{{ route('admin.bookings.index') }}"><i class="fa fa-briefcase
mr-2"></i>
      {{ __('Transaction') }}</a>
    </div>
  </div>
</li>
<!-- Nav Item - Lihat Website -->
<li class="nav-item">
  <a class="nav-link" href="#">
    <i class=""></i>
    <span>Lihat Website</span></a>
  </li>
</ul>

```