

DAFTAR PUSTAKA

- Amin, Shoifiul. 2016, Mechanics of Material, Bahan Ajar Program Studi Teknik Sipil.
- Bauchau, O.A dan Craig J.I. 2009, Structural Analysis, Springer, Atlanta.
- Bernitas, M.M. Ray, D. Kinley, P. 1981, KT, KQ and Efficiency for the Wagennigen B-Series Propellers, Departmen of Naval Architecture and Marine Engineering , Michigan
- BKI. 2019, Rules For Classification And Construction, Volume II.
- Dwi, N. 2016, Perencanaan Dan Analisa Struktur Parkir Rotari Kapasitas Delapan Mobil. Skripsi.
- Febrianto, N. 2018, Analysis Of Aluminium 8053 Connection Using Friction Stir Welding. Skripsi.
- Hardjono, S. 2012, Kajian Komparasi Ukuran Utama Kapal Penumpanga Katamaran Antara Bahan FRP Dan Aluminium, Volume 24 No.1.
- Kusna, D,I. dan Sofi'I, M. 2008, Teknik Konstruksi Kapal Baja Jilid 1 & 2, Direktorat Pembinaan Sekolah Menengah Kejuruan, Jakarta.
- Nafis, I. 2015, Kajian Teknis Dan Ekonomis Kapal Layanan Perbankan Menggunakan Material Aluminium. Skripsi.
- Pradana, H. dan Hidayat, I. 2016, Analisis Baban Statik Winglet N-219, INDEPT Vol 6 No.2.
- Pujo, Imam dan Septiadi, Ardi. 2011, Analisa Kekuatan Konstruksi Side Ramp Door Sistem Steel Wire Rope Pada KM. Dharma Kencana II Akibat Beban Statis Dengan Metode Elemen Hingga. Vol. 8 No. 3.

- Ship Structure Commite. 2013, SSC-464 High Speed Aluminium Vessels Design Guide.
- Simpson, J. 2003, Aluminium Boats Prove Their Mettle, The Aluminium Association
- Surdia, T. dan Saito, S. 1992, Pengetahuan Bahan Teknik, P.T Pradnya Paramita, Jakarta.
- Steels A. 2013, Aluminium Alloy Data Sheet 5083, Atlas Steels.
- Theodosius, G dan Saleh, M. 1985, Teori Soal Dan Penyelesaian Mekanika Teknik 1, Delta Teknik Group, Jakarta
- Wira, K. dkk. 2017, Analisa Kekuatan Struktur Pondasi Mesin Dengan Interaksi Trust Block Pada Kapal Ferry 500 GT Dengan Metode Elemen Hingga. Jurnal Teknik Perkapalan Vol.5, No.1
- Wirjosumarto, H dan Okumura, T. 2000, Teknologi Pengelasan Logam, P.T Pradnya Paramita, Jakarta
- Yulianto, T dan Ariesta, RC. 2019, Analisis Kekuatan Shaft Propeller Kapal Rescue 40 Meter dengan Metode Elemen Hingga. Jurnal Teknik Perkapalan Vol. 16, No.3

LAMPIRAN

Brosur mesin

Diesel Engines 12V/16V 4000 M71

for Vessels
with High Load Factors (1B)



Typical applications:
Ferries (e. g. Monohulls, Hydrofoils,
Catamarans, Surface Effect Ships)
and Yachts

Engine Model		12V 4000 M71	16V 4000 M71
Rated power ICFM	kW (bhp)	1850 (2480)	2465 (3305)
Speed	rpm	2000	2000
No. of cylinders		12	16
Bore/stroke	mm (in)	165/190 (6.5/7.5)	165/190 (6.5/7.5)
Displacement, total	l (cu in)	48.7 (2972)	65.0 (3967)
Flywheel housing		SAE 00	SAE 00
Coarbox model		ZF 7550	ZF 7550
		1 - 1.5 - 3.0	1 - 1.5 - 2.5

Performance and Fuel Consumption		12V 4000 M71			16V 4000 M71		
Speed	rpm	2000	1800	1200	2000	1800	1200
Maximum power	kW	1850	1750	770	2465	2395	1140
	bhp	2480	2345	1035	3305	3210	1530
Power on propeller curve (n)	kW	1850	1350	400	2465	1800	530
	bhp	2480	1810	535	3305	2415	719
Fuel consumption on propeller curve ¹⁾	g/kWh	209	209	213	209	211	213
	l/h	465.8	340.0	102.7	620.7	457.6	136.0
	gal/h	123.6	89.8	27.1	164.0	121.0	36.0

¹⁾ Tolerance +5% per ISO 3046, Diesel fuel to DIN EN 590 with a min L.H.V. of 42800kJ/kg (10290 BTU/lb)




Standard Equipment	
Starting System	Electric starter motor 24 V, 2 pole
Oil System	Gear driven lube oil pump, lube-oil duplex filter with diverter valve, centrifugal oil filter, lube-oil heat exchanger, handpump for oil extraction
Fuel System	Fuel delivery pump, fuel duplex filter with diverter valve, "Common Rail" fuel injection system with high-pressure pump, pressure accumulator and electronic fuel injection with cylinder cutout system, jacketed HP fuel lines, flame proof hose lines, leak-off fuel tank level monitored, fuel hand pump, fuel pre-filter with water separator
Cooling System	MTU-split-circuit coolant system, coolant-to-raw water plate core heat exchanger, self priming centrifugal raw water pump, gear driven coolant circulation pump, raw water connection for gearbox cooling
Combustion Air System	Engine coolant temperature-controlled intercooler, sequential turbocharging with 2 water-cooled turbochargers, on-engine set of seawater-resistant combustion-air filters
Exhaust System	Triple-walled, liquid-cooled, on-engine exhaust manifolds, exhaust bellows (horiz. discharge)
Mounting System	Resilient mounts
Power Transmission	Torsional and offset compensating couplings
Auxiliary PTO	Charging generator, 120A, 24V, 2 pole
Engine Management System	Engine control and monitoring system (MDEC), interface to gearbox control, interface to remote control and monitoring system, local operating panel (LOP)

Optional Equipment	
Starting System	Coolant preheating system
Oil System	Lube oil priming system
Cooling System	Engine version for sooted engine coolant system in conjunction with ship's side recooling system
Exhaust System	Exhaust outlet elbow (45°, 70°, 90°)
Auxiliary PTO	Bigpump
Engine Management System	In compliance with Classification Society Regulations
Monitoring / Control System	Fuel consumption measurement device (KRAL), monitoring and control system MCS-5, remote control system RCS-5
Gearbox Options	Various reverse reduction gearbox models, el. actuated, gearbox mounts, PTO for hydraulic pump at driving shaft or at mediate shaft, trolling, trailing pump, propeller shaft flange
Classification	ABS, BV, CCS, CR, DNV, GL, KR, LR, NK, RINA incl. necessary extensions to scope of supply

The rated power corresponds to ISO 3046-1:2002 [1] and ISO 15550:2002[2]. Intake air temperature 25°C / Sea water temperature 25°C; Intake air depression 15 mbar / Exhaust back pressure 30 mbar; Barometric pressure 1000 mbar. The power produced at the flywheel will be within the tolerance of 1.0% - according to ISO 15550:2002[2] - up to 45°C (113°F) combustion air temperature measured at the air cleaner inlet and up to 22°C (89.6°F) sea or raw water temperature measured at the sea water pump suction inlet. All engines fulfil IMO emission regulation. Emission- and classification- certificates are available on request. Specifications are subject to change without notice. All dimensions are approximate. For complete information refer to installation drawing. For further information consult your MTU dealer.

Dimensions and Masses (incl. gearbox)			
Engine Model		12V 4000 M71	16V 4000 M71
Length [L]	mm [in]	4055 (159.6)	4525 (178.1)
Width [W]	mm [in]	1520 (59.8)	1520 (59.8)
Height [H]	mm [in]	1890 (74.4)	1890 (74.4)
Mass [dry]	kg [lbs]	7 990 (17615)	9 210 (20304)



Tognum Group Companies

Europe / Middle East / Africa / Latin America
 MTU Friedrichshafen GmbH
 88040 Friedrichshafen
 Germany
 Phone +49 7541 907003
 Fax +49 7541 907081
 marineregion1@mtu-online.com
 www.mtu-online.com

Asia / Australia / Pacific
 MTU Asia Pte. Ltd.
 1, Benoi Place
 Singapore 629923, Republic of Singapore
 Phone +65 6861 5922
 Fax +65 6861 3615
 marineregion2@mtu-online.com
 www.mtu-online.com.sg

USA / Canada / Mexico
 MTU Detroit Diesel, Inc.
 13400 Outer Drive West
 Detroit, Michigan 48239, USA
 Phone +1 313 592 7806
 Fax +1 313 592 5137
 marineregion3@mtu-online.com
 www.mtudetroitdiesel.com

Subject to and limited by the latest of our data sheets
 MM 23 189 [02.15], Y 07 - MMA 2307-01